

761502



Detector unit LRS-S 700 - ESSER, German

**Approval: VdS**

As detector unit LRS 100 (761500) but with integrated scanner module and 12 x relay board. Enabling the unit to analyze up to 4 pipes separately. Four different areas can be monitored. This unit has 12 configurable potential-free contacts (10 NO contacts, 2 changeover contacts), instead of 7 in the LRS 100.

**Technical Data**

|                     |                                    |
|---------------------|------------------------------------|
| Operating voltage   | 18 ... 30 V DC                     |
| Current consumption | 240 mA to 500 mA                   |
| Contact load        | 30 V DC/1 A                        |
| Connection terminal | 0.2 bis 2.5 mm <sup>2</sup>        |
| Ambient temperature | 0 °C ... 39 °C                     |
| Air humidity        | 10% ... 95% (without condensation) |
| Type of protection  | IP30                               |
| Housing             | metal                              |
| Color               | gray                               |
| Weight              | approx. 3.5 kg                     |
| CE certificate      | 0832-CPD-0769                      |
| Specification       | EN 54-20 class A, B, C             |
| Dimensions          | W: 350 mm H: 225 mm D: 110 mm      |

762403



LRS-S 700 aspirating smoke detector - ESSER, English

**Approval: VdS**

As detector unit LRS 100 (761500) but with integrated scanner module and 12 x relay board. Enabling the unit to analyze up to 4 pipes separately. Four different areas can be monitored. This unit has 12 configurable potential-free contacts (10 NO contacts, 2 changeover contacts), instead of 7 in the LRS 100.



Connection via the 781331 / 781333 reset module (System 8000 / IQ8Control) and with additional 24V supply voltage.

762413



LRS-S 700 aspirating smoke detector - ESSER, French

762423



LRS-S 700 aspirating smoke detector - ESSER, Italian

762433



LRS-S 700 aspirating smoke detector - ESSER, Spanish