

FB inform./operating system, DIN A4 horizontal layout, individual locking-German



Part No.: 784725

Approval:

Description

Sheet steel housing with two leaves for surface mount or flush mount installation with central leaf opening for both door leaves. The right-hand housing door can be individually opened by means of a built-in CL1 lock. Door opening through fire brigade locking (suitable for half profile cylinder installation). In the left-hand half of the housing, a 784743 fire service indicator panel and a fire service operating panel 784710 are installed. The housing is designed for receiving a transmission unit or a manual call point. The fire service indicator panel is actuated via the serial interface in the control panel. The fire service operating panel is connected to the control panel interface. A maximum of 2 x 100 DIN A4 / horizontal layout fire brigade route maps can be integrated.

Technical Data

Operating voltage	10 ... 30 V DC
Quiescent current @ 12 V DC	approx. 50 mA
Alarm current @ 12 V DC	approx. 180 mA
Ambient temperature	-5 °C ... 40 °C
Storage temperature	-10 °C ... 60 °C
Type of protection	IP 30
Housing	sheet steel
Color	red, similar to RAL 3000
Weight	approx. 15 kg
Abmessungen	W: 710 mm H: 560 mm D: 100 mm

Additional information

Only in combination with the System 8000, IQ8Control fire detection panels. For redundant operation, redundancy module ADP-N3E (Part No. 784744) is required.

Downloads