

**25
Ports**



**50
Ports**



Front view



Rear view

Optronics category 3 High Density Voice Patch Panels offer a cost effective method for integrating voice circuits into standard structured cabling systems. Available in both 25 and 50 ports on a 1U 19" footprint they are ideal for maximising rack space.

Features

- > 19" rack mountable
- > Accepts 24-26 AWG
- > Supplied with fixings and earthing wire
- > IDC punch down
- > 25 or 50 RJ45 ports on 1U footprint
- > Integral cable management and grounding clamps

Applications

- > Voice integration into standard structured cabling systems

Conformance

- > Category 3
- > ISO/IEC 11801 : 2002
- > ANSI/EIA/TIA 568B.2 : 2002
- > UL approved

Technical Specifications

MECHANICAL	VALUE
Housing Material	PBT + 15% GF UL94V-0
Panel Frame	Carbon Steel, Powder Coating
Contact Material	PC UL94V-0 Contact: Phosphor Bronze + Nickel Plating
RJ45 Jack Life	Min 750 Insertions
IDC Life	Min 200 Terminations

Ordering Information

DESCRIPTION	PART NO
Optronics category 3 1U 25 Port Voice Patch Panel Black - UL approved	CAT3+LSA25
Optronics category 3 1U 50 Port Voice Patch Panel Black - UL approved	CAT3+LSA50