

SD-3001 R

OUTDOOR SIREN WITH OPTICAL AND ACOUSTICAL SIGNALING

An effective and rigid siren is one of key components of intruder security system. SATEL's product range includes a wide selection of different sirens, to suit almost any type of installation.

All these sirens provide several common features: high quality of components used, and advanced technology - just to make them reliable.

FEATURES

- microprocessor controlled
- acoustical signaling: dynamic horn
- optical signaling: xenon flash strobe
- inner metal shield
- tamper protection:
 - against removing from mounting surface
 - against opening
- support for sealed lead acid backup battery
- available also in blue (**SD-3001 BL**) and orange (**SD-3001 O**)



TECHNICAL SPECIFICATION

Power supply	12 V DC ±15%
Standby current consumption – without battery	35 mA
Maximum current consumption – without battery (optical signaling)	35 mA
Maximum current consumption – without battery (acoustic signaling)	1.7 A
Maximum current consumption – without battery (optical and acoustic signaling)	1.7 A
Sound pressure level (at 1 m distance)	up to 120 dB
Environmental class according to EN50130-5	III
Operating temperature range	-35°C...+55°C
Maximum humidity	93 ±3%
Housing dimensions	195 x 300 x 97 mm
Weight	1.21 kg