


Cable glands, metric, circular, earthing cones to VG 88773



Kabelverschraubungen, metrisch, rund, Erdungseinsatz nach VG 88773



Protection class to EN 60 529: IP 30; with shrink sleeves (e.g. to VG 95343-12) and connection thread gasket IP 66

Temperature range: -30°C to 80°C, interm. up to approx. 120°C

Material: - Cable gland: brass

- Earthing cones: brass chromium-plated

Equipment: Cable gland according to DIN 89280 for armoured cable

Schutzart gemäß EN 60 529: IP 30; mit Schrumpfschlauch (z.B. nach VG 95343-12) und Anschlussgewindedichtring IP 66

Einsatztemperatur: -30°C bis 80°C, kurzzeitig bis 120°C

Material: - Verschraubung: Messing

- Erdungskonen: Messing verchromt

Ausstattung: Kabeleinführung nach DIN 89280 aus Messing für Kabel mit Schirmung

Type	WISKA-No. bright / blank	WISKA-No. Cr						TL
				mm	mm	mm	mm	mm
KVM 16-VG A	10010893	10013924	1	M 16x1,5	10	· 10,5	17	40
KVM 18-VG A	10010894	10014693	1	M 18x1,5	10	· 11,5	19	43
KVM 18-VG B	10010895	10014444	1	M 18x1,5	10	11,5 · 12,5	19	43
KVM 24-VG A	10010896	10014383	1	M 24x1,5	11	· 11,5	24	49
KVM 24-VG B	10010897	10013950	1	M 24x1,5	11	11,5 · 13,5	24	49
KVM 24-VG C	10010898	10014214	1	M 24x1,5	11	13,5 · 16,5	24	49
KVM 30-VG A	10010899	10014694	1	M 30x2	12	16,5 · 18,0	30	52
KVM 30-VG B	10010900	10014445	1	M 30x2	12	18,0 · 19,5	30	52
KVM 30-VG C	10010901	10010120	1	M 30x2	12	19,5 · 20,5	30	52
KVM 36-VG A	10010902	10014695	1	M 36x2	13	20,5 · 22,5	36	58
KVM 36-VG B	10010903	10014384	1	M 36x2	13	22,5 · 25,5	36	58
KVM 45-VG A	10010904	10014340	1	M 45x2	14	25,5 · 27,5	46	62
KVM 45-VG B	10010905	10010126	1	M 45x2	14	27,5 · 31,5	46	62
KVM 56-VG A	10010906	10014250	1	M 56x2	15	31,5 · 34,0	55	68
KVM 56-VG B	10010907	10012073	1	M 56x2	15	34,0 · 37,5	55	68
KVM 56-VG C	10010908	10016462	1	M 56x2	15	37,5 · 41,0	55	68
KVM 72-VG A	10010909	10012074	1	M 72x2	16	41,0 · 46,0	70	73
KVM 72-VG B	10010910	10012148	1	M 72x2	16	46,0 · 50,5	70	73