


Reduction cable glands, metric, circular, type Z

Reduzier-Kabelverschraubungen, metrisch, rund, Typ Z



Protection class to EN 60 529: IP 54; installation with connection thread gasket IP 66
Temperature range: -40°C to 100°C, interm. up to approx. 120°C
Material: - Cable gland: brass (nickel-plated or chromium-plated on request)
 - Gasket: EPDM
Equipment: - Reduction cable gland acc. to DIN 89280 for armoured cable
 - * Similar to DIN 89280

Schutzart gemäß EN 60 529: IP 54; bei Montage mit Anschlussgewindedichtring IP 66
Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis 120°C
Material: - Verschraubung: Messing blank (vernickelt oder verchromt auf Anfrage)
 - Dichtung: EPDM
Ausstattung: - Reduzier-Kabeleinführung nach DIN 89280 für geschirmte Kabel
 - * Ähnlich DIN 89280

Type	WISKA No. bright / blank						TL
			mm	mm	mm	mm	mm
RVM 24/18-Z10A	10011223	1	M 24x1,5	11	8,0 · 10,5	19	44
RVM 30/18-Z10A	10011226	1	M 30x2	12	8,0 · 10,5	19	45
RVM 30/24-Z8A	10011227	1	M 30x2	12	7,0 · 8,5	24	50
RVM 30/24-Z10A	10011228	1	M 30x2	12	8,0 · 10,5	24	50
RVM 30/24-Z12	10011230	1	M 30x2	12	10,0 · 12,5	24	50
RVM 30/24-Z14	10011231	1	M 30x2	12	12,0 · 14,5	24	50
RVM 30/24-Z16	10011232	1	M 30x2	12	14,0 · 16,5	24	50
RVM 30/24-Z17	10011233	1	M 30x2	12	16,0 · 17,5	24	50
RVM 36/24-Z10A	10011235	1	M 36x2	13	8,0 · 10,5	24	51
RVM 36/24-Z12	10011237	1	M 36x2	13	10,0 · 12,5	24	51
RVM 36/24-Z14	10011238	1	M 36x2	13	12,0 · 14,5	24	51
RVM 36/24-Z16	10011239	1	M 36x2	13	14,0 · 16,5	24	51
RVM 36/24-Z17	10011240	1	M 36x2	13	16,0 · 17,5	24	51
RVM 36/30-Z18	10011241	1	M 36x2	13	16,0 · 18,5	30	53
RVM 36/30-Z20	10011242	1	M 36x2	13	18,0 · 20,5	30	53
RVM 45/30-Z18	10011243	1	M 45x2	14	16,0 · 18,5	30	54
RVM 45/30-Z20	10011244	1	M 45x2	14	18,0 · 20,5	30	54
RVM 45/36-Z20	10011245	1	M 45x2	14	18,0 · 20,5	36	59
RVM 45/36-Z22	10011246	1	M 45x2	14	20,0 · 22,5	36	59
RVM 45/36-Z24	10011247	1	M 45x2	14	22,0 · 24,5	36	59
RVM 45/36-Z26	10011248	1	M 45x2	14	24,0 · 26,5	36	59

Reduction cable glands, metric, circular, type Z

Reduzier-Kabelverschraubungen, metrisch, rund, Typ Z

Type	WISKA-No. bright / blank						TL
			mm	mm	mm	mm	mm
RVM 56/36-Z20	10011249	1	M 56x2	15	18,0 · 20,5	36	60
RVM 56/36-Z22	10011250	1	M 56x2	15	20,0 · 22,5	36	60
RVM 56/36-Z24	10011251	1	M 56x2	15	22,0 · 24,5	36	60
RVM 56/36-Z26	10011252	1	M 56x2	15	24,0 · 26,5	36	60
RVM 56/45-Z28	10011253	1	M 56x2	15	26,0 · 28,5	36	60
RVM 56/45-Z30	10011254	1	M 56x2	15	28,0 · 30,5	36	60
RVM 72/56-Z35	10011256	1	M 72x2	16	32,0 · 35,5	55	69
RVM 72/56-Z38	10011257	1	M 72x2	16	35,0 · 38,5	55	69
RVM 72/56-Z41	10011258	1	M 72x2	16	38,0 · 41,5	55	69
RVM 56/45-Z32	50011255	1	M 56x2	15	30,0 · 32,5	36	60