

## Holding Magnets with 490 N Holding Force

960126

**NEW**

### Wall mounted door magnet w/o release button, 490 N

Wall mounted direct current door magnet.

#### Technical Data

Operating voltage	24 V DC
Power consumption	1.5 W
Dimensions	W: 75 mm H: 116 mm D: 43 mm
Approvals	EN155, CPR, EN14637

767010



### Door retainer DH50-N490-WM

Door retainer with polarity reversal protection and connecting terminal including fixing plate for wall mounting.

#### Technical Data

Operating voltage	24 V DC
Power consumption	1.5 W
Dimensions	Ø: 50 mm H: 30 mm

## Holding Magnets with 800 N Holding Force

960119

**NEW**

### Door magnet with release button incl. flexible anchor, 800 N

Release button changeable to the left or right from the base. Cable entry is possible from behind the unit, as well as through the base, left or right side using included grommets.

In combination with angled mounting plates the unit can be installed to either floor or wall.

Integrated reverse-polarity protection diode and spark suppressing diode.

#### Technical Data

Operating voltage	24 V DC
Power consumption	2.2 W
Type of protection	IP54 (magnet); IP42 (connection)
Dimensions	W: 85 mm H: 110 mm D: 38 mm
Approvals	EN155, CPR, EN14637