

VERTICAL WIRE MANAGEMENT PANELS AND CABLE BRACKET HOLDERS



HVMP - 42



HVMF 42U

- Used for installation of vertical wire management panels, cable brackets (ordered separately) or additional 19" space in 800 mm wide free-standing racks
- Two designs: HVMF and HVMP
- HVMF – ready for cable management; compatible with VO-XX/YY and DP-VP-VR-XX
- HVMP – additional 3×1U 19" space (load rating 5 kg per position); compatible with separation frame
- Color: powder-coated RAL 9005

Code	Rack height (in U)	Package
HVMF-15	15	1 pair
HVMF-21	21	1 pair
HVMF-27	27	1 pair
HVMF-33	33	1 pair
HVMF-42	42	1 pair
HVMF-45	45	1 pair
HVMF-48	48	1 pair
HVMP-42	42	1 pair
HVMP-45	45	1 pair
HVMP-48	48	1 pair

VERTICAL WIRE MANAGEMENT PANELS




DP-VP-VR-42U

- Used for storing and managing cables vertically in 800 mm wide free-standing racks
- For racks 15–48U high
- 80×60 mm plastic duct for cable management
- Oval openings in base of ducts allow front to rear cabling
- Ducts with a minimum height of 33U have divided covers for easier handling
- Installed onto front of vertical extrusions using vertical wire holder; management panels (HVMF) – ordered separately
- Color: powder-coated RAL 9005


Code	Rack height (in U)	Package
DP-VP-VR-15	15	1 pc
DP-VP-VR-21	21	1 pc
DP-VP-VR-27	27	1 pc
DP-VP-VR-33	33	1 pc
DP-VP-VR-42	42	1 pc
DP-VP-VR-45	45, 48	1 pc

HORIZONTAL CABLE TRAY AND SIDE CABLE MANAGEMENT HOLDERS


HVMS-H-600



HVMS-H-800



HVMS-H-A



- HVMS-H-A: holder for HVMS-B, DP-UL at RSF or iSEVEN SERVER series with A-type extrusions, mounted on horizontal holders
- HVMS-H: for all rack series (recommended for RM7 and RI7), mounted on vertical extrusions
- Mounting kit included

Code	Used in rack sizes (mm)		Package
	RSF with A extrusions/RDF	iSEVEN family	
HVMS-H-A	All dimensions	–	1 pair
HVMS-H-600	–	600×600, 800×600	1 pair
HVMS-H-800	800×800	600×800, 800×800	1 pair

SIDE CABLE PERFORATED PANELS FOR A-TYPE EXTRUSIONS



DP-VV-A-42

- Used for storing and managing cables horizontally within the rack
- Used in free-standing racks 42–48U in high
- Available width – 100 mm
- Installation directly in top and bottom frame of the PREMIUM rack or iSEVEN SERVER (with A type extrusions only)
- Installation kit is included in delivery

Code	Used in rack height (U)	Package
DP-VV-A-42	42	1 pc
DP-VV-A-45	45	1 pc
DP-VV-A-48	48	1 pc