

**5341FE Multi-Conductor - Commercial Applications**

For more Information  
please call

1-800-Belden1

**General Description:**

Security & Alarm Cable, Riser-CMR, 2-18 AWG stranded bare copper pairs with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

**Physical Characteristics (Overall)****Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
2	18	7x26	BC - Bare Copper

Total Number of Conductors: 4

**Insulation****Insulation Material:**

Insulation Material	Wall Thickness (mm)
PP - Polypropylene	0.178

**Outer Shield****Outer Shield Material:**

Outer Shield Trade Name	Outer Shield Material
Beldfoil®	Aluminum Foil-Polyester Tape

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
24	Solid	TC - Tinned Copper

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.432

**Overall Cable**

Overall Nominal Diameter: 6.350 mm

**Pair****Pair Color Code Chart:**

Number	Color
1	Black & Red
2	Black & White

**Mechanical Characteristics (Overall)**

Operating Temperature Range: -20°C To +70°C

Bulk Cable Weight: 49.111 Kg/Km

Max. Recommended Pulling Tension: 460.834 N

Min. Bend Radius/Minor Axis: 63.500 mm

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification: CMR

## 5341FE Multi-Conductor - Commercial Applications

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire &amp; Cable): Yes

MII Order #39 (China RoHS): Yes

## Flame Test

UL Flame Test: UL1666 Vertical Shaft

CSA Flame Test: FT4

## Plenum/Non-Plenum

Plenum (Y/N): No

## Surface Printing (Overall)

Surface Printing: NEW GENERATION(R) BY BELDEN 5341FE CMR 75C 2PR18 SHIELDED (UL) E108998 OR C(UL) CMG----FT4 (2 FT., 7 DIGIT SEQUENTIAL) FEET

## Electrical Characteristics (Overall)

## Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

95.149

## Nom. Capacitance Cond. to Other Conductor &amp; Shield:

Capacitance (pF/m)

171.432

## Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

21.4905

## Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

42.981

## Max. Operating Voltage - UL:

Voltage

300 V RMS

## Max. Recommended Current:

Description Current

10C Temperature Rise 4 Amps per conductor @ 25°C ambient

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5341FE 008U1000	1,000 FT	35.000 LB	GRAY		2 PR #18 PP FS FRPVC
5341FE 008Z1000	1,000 FT	37.000 LB	GRAY		2 PR #18 PP FS FRPVC
5341FE 0081000	1,000 FT	37.000 LB	GRAY	C	2 PR #18 PP FS FRPVC
5341FE 0081200	1,200 FT	43.200 LB	GRAY		2 PR #18 PP FS FRPVC
5341FE 0081500	1,500 FT	54.000 LB	GRAY		2 PR #18 PP FS FRPVC
5341FE 008500	500 FT	19.000 LB	GRAY	C	2 PR #18 PP FS FRPVC

## Notes:

C = CRATE REEL PUT-UP.

## 5341FE Multi-Conductor - Commercial Applications

Revision Number: 3    Revision Date: 08-20-2013

© 2019 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).