

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

A0407005 Faceplates and Panels - MDVO SC Module MM





For more Information please call

1-800-Belden1



General Description: MDVO Module SC Simplex Multimode, White Usage (Overall) Suitable Applications: FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room Related Parts: Compatible MDVO-style Faceplate and Patch Panel, SC Fiber Patch Cord Physical Characteristics (Connectivity) Capacity Capacity Access Front Connection: Flush Termination Area: SC Dimensions: Buschington Widdit mom Depth mom 17.018 17.018 33.274 Materials Materials Materials: Duscription Phashor Bronze Weight 0.006 kg Included Parts: Dust Caps Packaging 10 units packaged in a plastic bag.				
Usage (Overall) Suitable Applications: FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room Related Parts: Compatible MDVO-style Faceplate and Patch Panel, SC Fiber Patch Cord Physical Characteristics (Connectivity) Capacity Access Front Connection: Flush Termination Area: SC Dimensions Dimensions: Height (mm) Width (mm) Depth (mm) 17.018 33.274 Materials: Materials: Weight 0.006 kg Weight: 0.006 kg Included Parts: Dust Caps Packaging 10 units packaged in a plastic bag.	General Description:			
Suitable Applications: FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room Related Parts: Compatible MDVO-style Faceplate and Patch Panel, SC Fiber Patch Cord Physical Characteristics (Connectivity) Capacity Capacity Front Connection: Front Connection: Flush Termination Area: SC Dimensions SC Dimensions: Height (mm) Width (mm) Depth (mm) 17.018 17.018 33.274 Materials Materials Materials: Pleastic - UL94V-0 Connector Body SC-Simplex Polymer Sieeve Phosphor Bronze Weight Weight: 0.006 kg Included Parts: Dust Caps Packaging 10 units packaged in a plastic bag.	MDVO Module SC Simplex Multimode, White			
Distribution Room Related Parts: Compatible MDVO-style Faceplate and Patch Panel, SC Fiber Patch Cord Physical Characteristics (Connectivity) Capacity Access Front Connection: Flush Termination Area: SC Dimensions Dimensions: Height (mm) Width (mm) Depth (mm) 17.018 17.018 17.018 17.018 Sc Materials: Description Type Materials Weight 0.006 kg Included Parts: Dust Caps Packaging Packaging: 10 units packaged in a plastic bag.	Usage (Overall)			
Physical Characteristics (Connectivity) Capacity Access Front Connection: Flush Termination Area: SC Dimensions: Height (mm) Width (mm) Depth (mm) 17.018 17.018 17.018 17.018 33.274 Materials Materials: Description Type Plastic - UL94V-0 Connector Body SC-Simplex Polymer Sileeve 0.006 kg Weight 0.006 kg Included Parts Dust Caps Packaging 10 units packaged in a plastic bag.				
Capacity Access Front Connection: Flush Termination Area: SC Dimensions: SC Height (mm) Width (mm) Depth (mm) 17.018 17.018 17.018 17.018 Materials: Materials: Veight Weight 0.006 kg Included Parts Dust Caps Packaging 10 units packaged in a plastic bag.	Related Parts:	Compatible MDVO-style Faceplate and Patch Panel, SC Fiber Patch Cord		
Capacity Access Front Connection: Flush Termination Area: SC Dimensions Dimensions: SC Height (mm) Width (mm) Depth (mm) 17.018 17.018 17.018 17.018 Materials Materials: Materials: Veight Weight Weight Weight: 0.006 kg Included Parts Dust Caps Packaging Packaging: 10 units packaged in a plastic bag.	Physical Characteristics (Connectivity)			
Termination Area: SC Dimensions Dimensions: Image: Insert is materials: Image: Insert is material is				
Dimensions Dimensions: Height (mm) Width (mm) Depth (mm) 17.018 33.274 Materials Materials: Description Type Material Insert Plastic - UL94V-0 Connector Body SC-Simplex Polymer Sleeve Connector Body SC-Simplex Polymer Sleeve Phosphor Bronze Weight Weight: 0.006 kg Included Parts Included Parts: Dust Caps Packaging Packaging: 10 units packaged in a plastic bag.	Front Connection:	Flush		
Dimensions: Height (mm) Width (mm) Depth (mm) 17.018 17.018 33.274 Materials Materials: Description Type Materials: Description Type Plastic - UL94V-0 Connector Body SC-Simplex Polymer Sleeve Phosphor Bronze Weight Weight: 0.006 kg Included Parts Included Parts: Dust Caps Packaging: Packaging: 10 units packaged in a plastic bag.	Termination Area:	SC		
Sleeve Phosphor Bronze Weight 0.006 kg Included Parts Dust Caps Packaging 10 units packaged in a plastic bag.	Height (mm) Width (mm) Depth (mm)17.01817.01833.274MaterialsDescriptionTypeMaterialInsertPlastic - UL94V-0			
Weight: 0.006 kg Included Parts Dust Caps Packaging Packaging: 10 units packaged in a plastic bag.	Sleeve Phosphor Bronze			
Included Parts: Dust Caps Packaging 10 units packaged in a plastic bag.	-	0.006 kg		
Packaging: 10 units packaged in a plastic bag.	Included Parts:	Dust Caps		
Mechanical Characteristics (Connectivity)		10 units packaged in a plastic bag.		
	Mechanical Characteristics (Connectivity)			
Footprint/Type: MDVO-Style	Footprint/Type:	MDVO-Style		
Storage Temperature Range: -40°C To +70°C	Storage Temperature Range:	-40°C To +70°C		
Installation Temperature Range: -10°C To +60°C	Installation Temperature Range:	-10°C To +60°C		

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

A0407005 Faceplates and Panels - MDVO SC Module MM

Operating Temperature Range:	-10°C To +60°C
Applicable Specifications and Agency Co	ompliance (Overall)
Applicable Standards & Environmental Prog	rams
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
MII Order #39 (China RoHS):	Yes
Suitability	
Suitability - Indoor:	Yes

Notes (Overall)

Notes: For additional information about this product, visit our web site at http://www.belden.com

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
A0407005	1 EA	0.017 LB			MDVO SC FIBER MODULE,

Revision Number: 0 Revision Date: 04-01-2015

© 2019 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.