Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

AX101852 Modular Connectors - Termination Station

		For more Information please call
		1-800-Belden1
General Description:		
Termination Station		
Usage (Overall)		
Suitable Applications:	Terminate 10GX, CAT6+, Cat5E MDVO and Keyconnect S	tyle Module, Mediaflex Gigaflex Inserts
Related Parts:	10GX, CAT6+, Cat5E MDVO and Keyconnect Style Modul	e, Mediaflex Gigaflex Inserts
Physical Characteristics (Connectivity)		
Dimensions Dimensions: Height (mm) Width (mm) Depth (mm) 63.500 142.240 177.800 Materials Materials:		
Description Material Termination Station Plastic - UL940V-0		
Color	5	
Color:	Black	
Weight Weight:	0.045 kg	
Packaging	·	
Packaging:	Individually packaged in a clear plastic bag, Standard ship	ping carton of 10 units
Mechanical Characteristics (Connectivity)		
Storage Temperature Range:	-40°C To +70°C	
Installation Temperature Range:	-10°C To +60°C	
Applicable Specifications and Agency Complianc Suitability	e (Overall)	
Suitability - Indoor:	Yes - Indoor	
Transmission Characteristics (Connectivity)		
Notes (Overall)		
Notes: For proper installation refer to Installation Guide PX1032	206 available on our web site at http://www.belden.com	
Product Family		
Put Ups and Colors:		

AX101852 1 EA 0.333 LB BLACK MEDIAFLEX TERMINATION STATION	Item #	Putup	Ship Weight	Color	Notes	Item Desc
	AX101852	1 EA		BLACK		MEDIAFLEX TERMINATION STATION

Revision Number: 0 Revision Date: 06-05-2009

© 2016 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.