


1101A Multi-Conductor - Thermocouple Extension Cable

For more Information
please call

1-800-Belden1

**Description:**

16 AWG pairs solid conductors, overall Beldfoil shield (100% coverage), PVC insulation, PVC jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
1	16	Solid	Chromel & Constantan

Total Number of Conductors: 2

Insulation**Insulation Material:**

Insulation Material	Wall Thickness (mm)	Dia. (mm)
PVC - Polyvinyl Chloride	0.4318	2.159

Outer Shield**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
18	16x30	TC - Tinned Copper

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord: Yes

Overall Cable

Overall Nominal Diameter: 6.299 mm

Pair**Pair Color Code Chart:**

Number	Color
1	Purple & Red

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +105°C

Non-UL Temperature Rating: 105°C

Bulk Cable Weight: 56.552 Kg/Km

Min. Bend Radius/Minor Axis: 63.500 mm

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification: CMG, PLTC, ITC

CEC/C(UL) Specification: CMG

1101A Multi-Conductor - Thermocouple Extension Cable

EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
ANSI Specification:	MC 96.1-1982 Type EX

Flame Test

UL Flame Test:	UL1685 FT4 Loading
CSA Flame Test:	FT4
ICEA Flame Test:	T-29-520

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (μH/m)
0.59058

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
167.331

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
82.025

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/km)
CHROMEL	541.365
CONSTANTAN	397.001

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
124.678

Notes (Overall)

Notes: Chromel & Constantan = "Constantan is a Hoskins Manufacturing Company trademark."

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1101A 0071000	305 MT	19.958 KG	VIOLET	C	2 #16 PVC FS PVC
1101A 00710000	3,048 MT	213.189 KG	VIOLET	C Z	2 #16 PVC FS PVC
1101A 0075002	1,524 MT	38.100 FT			300V/EX/PR/01/16AWG/PVC/OS/NIA

Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

1101A Multi-Conductor - Thermocouple Extension Cable

Revision Number: 1 Revision Date: 05-14-2007

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.