

Security and Alarm Cables

Commercial Applications Shielded




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

22 AWG • Stranded (7x30) 0.8 mm Bare Copper • Beldfoil® Shield • 24 AWG Tinned Copper Drain Wire • Numbered and Color Coded

PVC Insulation • Grey PVC Jacket

300V 75°C	NEC: CMR CEC: CMG FT4						0.76 mm 22 AWG (7x30) BC	0.040	1.01	Overall Beldfoil® + Drain Wire (24 AWG TC)		see chart below	
--------------	--------------------------------	--	--	--	--	--	--------------------------------	-------	------	---	--	-----------------	--



5500FE	2 CDR	C-500	C-152	5.5	2.5						0.130	3.30		
		U-500	U-152	6.6	3.0									
		500	152	6.6	3.0									
		U-1000	U-305	11.9	5.4									
		1000	305	11.9	5.4									
5501FE	3 CDR	C-500	C-152	7.1	3.2						0.138	3.51		
		U-500	U-152	7.9	3.6									
		500	152	7.5	3.4									
		U-1000	U-305	15.0	6.8									
		1000	305	15.0	6.8									
5502FE	4 CDR	C-500	C-152	8.6	3.9						0.152	3.86		
		U-500	U-152	9.5	4.3									
		500	152	9.5	4.3									
		U-1000	U-305	18.1	8.2									
		1000	305	18.1	8.2									
5503FE	5 CDR	1000	305	22.0	10.0						0.165	4.19		
5504FE	6 CDR	C-500	C-152	13.4	6.1						0.179	4.55		
		U-500	U-152	15.0	6.8									
		U-1000	U-305	29.1	13.2									
		1000	305	29.1	13.2									
5506FE	8 CDR	U-500	U-152	16.5	7.5						0.196	4.98		
		U-1000	U-305	32.0	14.5									
		1000	305	32.0	14.5									
5508FE	10 CDR	U-500	U-152	19.6	8.9						0.230	5.84		
		U-1000	U-305	37.9	17.2									
		1000	305	44.1	20.0									

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance

Color Code

Cond. No.	Color
1	Black
2	Red
3	White
4	Green
5	Brown

Color Code

Cond. No.	Color
6	Blue
7	Orange
8	Yellow
9	Purple
10	Grey