

Part Number: 85102 Electronic, 2 C #16 Str TC, ETFE Ins, ETFE Jkt

Product Description

High Temperature Electronic, 2 Conductor 16AWG (19x29) Tinned Copper, ETFE Insulation, ETFE Outer Jacket

Technical Specifications

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	No. of	Conductors
16	19x29	TC - Tinned Copper	2	
Conductor Count:		2		
Total Number of Pairs:		1		

Insulation

Material	Material Trade Name	Nominal Wall Thickness
ETFE - Ethylene Tetrafluoroethylene	Tefzel®	0.0135 in

Color Chart

Number	Color
1	Black
2	White

Outer Shield Material

Material Unshielded

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
ETFE - Ethylene Tetrafluoroethylene	Tefzel®	0.211 in	0.019 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 4.76 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor 20 pF/ft

Inductance

Nominal Inductance

0.17 µH/ft

Current

Max. Recommended Current [A] 9.5 Amps per conductor @ 25°C

Voltage

Non-UL Voltage Rating

300 V RMS

Temperature Range

Non-UL Temp Rating:	150°C
Operating Temp Range:	-60°C To +150°C

Mechanical Characteristics

Bulk Cable Weight:	28 lbs/1000ft
Max Recommended Pulling Tension:	61 lbs
Min Bend Radius/Minor Axis:	2.25 in

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
Plenum/Non-Plenum	

Plenum (Y/N):	No

Part Number

Variants

Item #	Color	UPC	Length	Footnote
85102 3681000	Clear, Transparent	612825210580	1,000 ft	С
85102 368500	Clear, Transparent	612825210597	500 ft	С
Footnote:		C	CRATE F	REEL PUT-L

Product Notes

Notes:	Tefzel is a trademark of Dupont.		
History			
Update and Revision:	Revision Number: 0.276 Revision Date: 08-22-2019		

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.