

Part no.	DKA type	Cross Sectional Area	Rated voltage	Overall dimensions approx. [w x t]	Data elements	Weight approx.	Copper Content	Supporting members	Loop	Suspension device	Standards
		[n x mm ²]	U ₀ /U [V]	[mm x mm]		[kg/100m]	[kg/km]		[mm]		
165 342	6599-F	20 G 0.75	300/500	62.8 x 4.3	none	46.5	144	HTF	300	LZ 1009	
165 344	6599-F	24 G 0.75	300/500	73.1 x 4.3	none	54.9	173	HTF	300	LZ 1009	
156 879	7770-F	24 G 0.75	300/500	73.2 x 4.3	none	59.0	173	ST Ø 2.5	400	LZ 1009	
166 618	6599-F	18 G 1.00	300/500	58.6 x 4.4	none	47.3	173	HTF	300	LZ 1009	
166 505	6599-F	24 G 1.00	300/500	75.4 x 4.4	none	63.0	230	HTF	300	LZ 1009	
G=green-yellow											
Part no.	DKA type	Cross Sectional Area	Rated voltage	Overall dimensions approx. [w x t]	Data elements	Weight approx.	Copper Content	Supporting members	Loop	Suspension device	Standards
		[n x mm ²]	U ₀ /U [V]	[mm x mm]		[kg/100m]	[kg/km]		[mm]		
155 425	7757-F	4 G 1.00 + 16 x 0.75 + 2 x 4 x 0.25 + 1 x 2 x 0.25	300/500 300/500 250/250 250/250		7067/2-F 7954/2-F	65.9	187	ST Ø 2.5	450	LZ 1009	
176 877	6900-F	6 G 1.50 + 6 x 1.00 + 1 x 4 x 0.50	450/750 300/500 300/300	53.0 x 6.4	6347/3-F	59.6	173	HTF	400	LZ 1006	
166 612	7500-F	12 G 1.00 + HF 75	300/500	50.9 x 6.4	HF-2120/1-F	53.0	139	HTF	400	LZ 1006	
177 690	8666-F	12 G 1.00 + 1 x 4 x 0.34	300/500 300/300	50.9 x 6.4	8607-F	52.5	142	HTF	400	LZ 1006	
167 088	7757-F	4 G 1.50 + 16 x 1.00 + 2 x 2 x 0.50 + 1 x 2 x 0.50	450/750 300/500 300/300 300/300	78.5 x 5.8	7067/2-F 7954/2-F	84.3	250	ST Ø 2.5	450	LZ 1009	
168 190	8483-F	4 G 1.50 + 16 x 1.00 + 3 x 2 x 0.50	450/750 300/500 300/500	79.7 x 6.1	7954/2-F	89.6	275	ST Ø 2.5	450	LZ 1010	
167 018	8210-F	2 x 1.50 + HF 75 + 8 x 2 x 0.50	450/750 300/300	54.1 x 7.1	HF-2120/1-F 6651-F	58.0	149	HTF	450	LZ 1006	
168 191	8210-F	4 x 1.50 + 2 HF 75 + 8 x 2 x 0.50	450/750 300/300	64.3 x 7.0	HF-2120/1-F 6651-F	71.6	201	HTF	450	LZ 1009	
182 058	8820-F	4 x 1.50 + 2 HF 75 + 8 x 2 x 0.50	450/750 300/300	64.3 x 7.0	HF-2120/1-F 6651-F	74.5	201	ST Ø 2.5	500	LZ 1009	
185 217	8210-F	4 x 1.50 + 4 HF 75 + 8 x 2 x 0.50	450/750 300/300	72.8 x 7.0	HF-2120/1-F 6651-F	82.5	249	HTF	450	LZ 1009	
168 185	8507-F	12 x 2 x 0.50	300/300	54.1 x 5.6	6651-F	44.9	147	HTF	400	LZ 1006	
192 360	8854/3-H	4 x 2 x 0.50	300/300	28.0 x 9.0	6651/3-H	31.1	56	ST Ø 2.5	450	LZ 1006	
191 093	8512-F	3 G 2.50 + 14 x 1.00 + 4 x 2 x 0.50	450/750 300/500 300/300	79.0 x 5.7	6651-F	80.6	232	ST Ø 2.5	400	LZ 1009	