



Fig. 1:
ecobus® Power Adapter
3 x Power



Fig. 2:
ecobus® Power Adapter
5 x Power



Fig. 3:
ecobus® Power Adapter-S
5 x Power

Product information

Application

For permanently connecting the ecobus® Power cable in dry areas without the need to remove cable sheathing.

General Properties

Housing	Polyamide 6,6, phase L1 light grey, phase L2 dark grey, Phase L3 black
Slider	Polyamide 6,6, glass-fibre reinforced, black
Cap	Polycarbonate, transparent
Power current screw	Silver-plated brass, for posidrive no. 2 screwdriver
Test Specifications	IEC 60998-1, IEC 60998-2-3, Provisional IEC 61535 and VDE 0628
Housing	Flammability according to UL Standard 94: V-2
Slider and Cap	Flammability according to UL Standard 94: V-0
Slider	Halogen-free
Connection	Glass-fibre: 25%
	Output on side with confusion-free jacks or on the end for article no 301 076 ecobus® Combi Connector-S

Article No. 1301 075:
One packaging unit contains 48 items, 16 each of L1, L2 and L3.
The phases can be distributed evenly by corresponding assembly.

Further Information

correct plugs for 1301 075 see page E-30
correct plugs for 1301 077 see page E-32

See Fig. 1: ecobus® Power Adapter / (L1/L2/L3)

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
1301 075	3 x 2,5	40	57,5 x 34,5 x 25,7	0,178	16 x L1 + 16 x L2 + 16 x L3
1300 972	3 x 2,5	40	57,5 x 34,5 x 25,7	0,178	50 x L1
1300 973	3 x 2,5	40	57,5 x 34,5 x 25,7	0,178	50 x L2
1301 074	3 x 2,5	40	57,5 x 34,5 x 25,7	0,178	50 x L3

See Fig. 2: ecobus® Power Adapter

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
1301 077	5 x 2,5	64,5	57,5 x 54 x 25,7	0,271	50

See Fig. 3: ecobus® Power Adapter-S

Article No.	for nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
1301 076	5 x 2,5	60	53 x 41 x 39	0,329	50