


FO Outdoor ZGGT HP / A-DQ(ZN)B2Y

HighP Euroclass Fca

central tube design, metal-free,
longitudinally watertight, rodent protection



- 1 ≤ 24 fibres
- 2 Loose tube
- 3 Glass armour
- 4 Ripcord
- 5 HDPE sheath



DESCRIPTION

Robust, metal-free fibre optic outdoor cable with one central loose tube and up to 24 fibres.
High tensile strength and high radial load strength for the highest transmission security.
Lightweight and installation friendly cable construction.
Non-metallic rodent protection.
The two coloured ripcords are easy to identify and enable the safe opening of the cable sheath.
HDPE cable sheath, easy to lay.

APPLICATION

For pulling in or blowing through thermoplastic duct systems.
Suitable for laying in cable platforms, cable shafts
and even in very complex cable trays.
Direct burial.

OPTICAL PROPERTIES

The cables are available with different types of optical fibre (see fibre data sheets).

MECHANICAL PROPERTIES

Temperature range	storage: during installation: in operation:	-40 / +70°C -10 / +50°C -40 / +60°C	IEC 60794-1-22 F1
Tensile performance:	IEC 60794-1-21 E1		
Crush resistance:	IEC 60794-1-21 E3		
Impact:	IEC 60794-1-21 E4		
Repeated bending:	IEC 60794-1-21 E6		
Torsion:	IEC 60794-1-21 E7		
Bend:	IEC 60794-1-21 E11		
Water penetration:	IEC 60794-1-22 F5		

STANDARDS

Reaction to fire (Euroclass)	EN 13501-6: F _{ca}
Imprint	DATWYLER «cable type» «Datwyler designation» «DIN designation» «no. of fibres» «fibre type» «add. text» «batch no.» «meter marks»
Zero halogen, no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2

VERSIONS

Article No.	DoP	Product	Reaction to fire (Euroclass)	Number of fibres	Loose Tubes	Sheath colour	Fibre type	Sheath Ø [mm]	Weight [kg/km]	Bending radius [mm]	Tensile load [N]	Crush resistance continuous [N]	Crush resistance short term [N]	Fire load [kWh/m]	PU
19016600FZ		FO Outdoor HP 1x4	Fca	4	1	black	E9/125 G.652.D OS2	8.2	75	130	2500	6000	10000	0.558	by the metre
19212100FZ		FO Outdoor HP 1x4	Fca	4	1	black	G50/125 OM3	8.2	75	130	2500	6000	10000	0.558	by the metre
19608900FZ		FO Outdoor HP 1x4	Fca	4	1	black	G50/125 OM4	8.2	75	130	2500	6000	10000	0.558	by the metre
19016700FZ		FO Outdoor HP 1x6	Fca	6	1	black	E9/125 G.652.D OS2	8.2	75	130	2500	6000	10000	0.558	by the metre
19074700FZ		FO Outdoor	Fca	6	1	black	G50/125	8.2	75	130	2500	6000	10000	0.558	by the

FO Outdoor ZGGT HP / A-DQ(ZN)B2Y

HighP Euroclass Fca

central tube design, metal-free,
longitudinally watertight, rodent protection



		HP 1x6				OM3									metre
19016800FZ		FO Outdoor Fca	8	1	black	E9/125 G.652.D OS2	8.2	75	130	2500	6000	10000	0.558	by the metre	
19609000FZ		FO Outdoor Fca	8	1	black	G50/125 OM4	8.2	75	130	2500	6000	10000	0.558	by the metre	
19016900FZ		FO Outdoor Fca	12	1	black	E9/125 G.652.D OS2	8.2	75	130	2500	6000	10000	0.558	by the metre	
18636100FZ		FO Outdoor Fca	12	1	black	G50/125 OM3	8.2	75	130	2500	6000	10000	0.558	by the metre	
19261000FZ		FO Outdoor Fca	12	1	black	G50/125 OM4	8.2	75	130	2500	6000	10000	0.558	by the metre	
19014900FZ		FO Outdoor Fca	24	1	black	E9/125 G.652.D OS2	8.6	80	135	2500	6000	10000	0.589	by the metre	
19264500FZ		FO Outdoor Fca	24	1	black	G50/125 OM3	8.6	80	135	2500	6000	10000	0.589	by the metre	
19216700FZ		FO Outdoor Fca	24	1	black	G50/125 OM4	8.6	80	135	2500	6000	10000	0.589	by the metre	