## FIBRE OPTIC PANELS & ENCLOSURES

## FO patch panel OV-A / OV-AT

19"/1U, unloaded

exchangeable front plate, extractable, depth-adjustable mounting



Fibre optic patch panel OV-AT, 19"/1U, without front plate, extractable, depth-adjustable mounting

## **PRODUCT INFORMATION**

**APPLICATION** For the termination of fibre optic cables (breakout, loose tube) - maximum of 48 fibres.

Applicable with a wide range of front plates / connector systems (see OV-A / OV-AT 1U accessories).

**DESCRIPTION** Housing: metallic, extractable drawer (OV-A) or drawer with

telescopic slides (OV-AT), both with locking mechanism
Rack mounting: depth-adjustable mounting of box (5 steps, maximum 50 mm)

due to the adjustable 19" mounting brackets

Colour (variants): similar to RAL 7035, similar to RAL 9005 and stainless steel

Imprint: numbers (silk screen printing) on frontplate (to be ordered seperately)

Capacity: up to 48 fibres

Strain relief: with cable tie and screwed cable gland or cable distributor

Cable entry: rear left and right
Dimensions: 19"/1U, depth 254 mm

**CONNECTOR SYSTEM** Adapter: ST, FC, SCD, SC, LSH, LCD

**SCOPE OF DELIVERY** Box, strain relief with M20 (1U) cable gland,

splice tray holder and adhesive fibre fixation (3 pcs.)

Please order the front plate seperately.

Article No.	Description	Colour (similar to)	Note
416950	OV-A extractable 1U	RAL 7035	without front plate
416964	OV-AT telescopic 1U	RAL 7035	without front plate
417376	OV-A extractable 1U	RAL 9005	without front plate
416975	OV-AT telescopic 1U	stainless steel	without front plate
416959	Telescopic slides for upgrading OV-A to OV-AT		
1405304	Label for OV-A and OV-AT, self-adhesive, length 420 mm		

