

## Distribution blocks

### Three-pole distribution blocks, three outlets

Installation screws max.  $\varnothing$  3.5 mm, holes 28 mm apart.

Product code	GTIN	Description	Weight	Package
NAD3.W	6418677113284	One inlet, three outlets, white	35.1 g	10/50
NAD3.B	6418677114793	One inlet, three outlets, black	35.1 g	10/50
NBD3.S	6418677116148	One inlet, three outlets, blue	35.1 g	10/50
NCD3.G	6418677117176	One inlet, three outlets, grey	35.1 g	10/50
NCD3.P	6418677117459	One inlet, three outlets, red	35.1 g	10/50



### Three-pole distribution blocks, seven outlets

The distribution blocks are fixed with four screws (max.  $\varnothing$  4.2 mm). No separate mounting pad is required if the distribution block is installed partially inside a lighting rail with a minimum width of 70 mm.

Product code	GTIN	Description	Weight	Package
NAD36.W	6418677724152	One inlet, seven outlets, white	104.2 g	10
NAD36.B	6418677724169	One inlet, seven outlets, black	104.2 g	10
NBD36.S	6418677724176	One inlet, seven outlets, blue	104.2 g	10
NCD36.G	6418677724183	One inlet, seven outlets, grey	104.2 g	10
NCD36.P	6418677724190	One inlet, seven outlets, red	104.2 g	10



### Four-pole T-distributor, two outlets

A plug coupler can be connected to the device with a cable or mounted on the frame of the device with a panel mounting adapter, which is sold separately.

Product code	GTIN	Description	Weight	Package
NAD4T.W	6418677703652	One inlet, two outlets, white	30.2 g	10/50



### Four-pole T-distributor, two outlets, a separate locking device on the side branch

The component can be used when the device does not have space for the standard plane mounting adapter. A plug coupler can be connected to the device with a cable or mounted on the frame of the device with a narrow plane mounting adapter, which is sold separately.

Product code	GTIN	Description	Weight	Package
NAD4TH3.W	6418677703669	One inlet, two outlets, white, no locking latches on the side branch	29.4 g	10/50



### Five-pole T-distributors, two outlets

A plug coupler can be connected to the device with a cable or mounted on the frame of the device with a panel mounting adapter, which is sold separately.

Product code	GTIN	Description	Weight	Package
NAD5T.W	6418677716645	One inlet, two outlets, white	37.7 g	10/50
NAD5T.B	6418677716652	One inlet, two outlets, black	37.7 g	10/50
NCD5T.G	6418677716669	One inlet, two outlets, grey	37.7 g	10/50
NCD5T.P	6418677716676	One inlet, two outlets, red	37.7 g	10/50



### Five-pole Linect T-block, two outlets

Linect T-block with a supply and outlet, specifically designed for DALI-controlled dimming. The T branch is connected to the lighting fixture with a Linect screwless coupler. Linect code I - blue

Product code	GTIN	Description	Weight	Package
NCD5LI.G	6418677724466	Linect T-block, five poles, C/I code (1, N, PE, a+, b-)	71 g	10/50

