

Distribution blocks

Three-pole distribution blocks, three outlets

Installation screws max. \varnothing 3.5 mm, holes 28 mm apart.

Product code	GTIN	Description	Weight	Package
NAD3.W	6418677113284	One inlet, three outlets, white	35.1 g	10/50
NAD3.B	6418677114793	One inlet, three outlets, black	35.1 g	10/50
NBD3.S	6418677116148	One inlet, three outlets, blue	35.1 g	10/50
NCD3.G	6418677117176	One inlet, three outlets, grey	35.1 g	10/50
NCD3.P	6418677117459	One inlet, three outlets, red	35.1 g	10/50



Three-pole distribution blocks, seven outlets

The distribution blocks are fixed with four screws (max. \varnothing 4.2 mm). No separate mounting pad is required if the distribution block is installed partially inside a lighting rail with a minimum width of 70 mm.

Product code	GTIN	Description	Weight	Package
NAD36.W	6418677724152	One inlet, seven outlets, white	104.2 g	10
NAD36.B	6418677724169	One inlet, seven outlets, black	104.2 g	10
NBD36.S	6418677724176	One inlet, seven outlets, blue	104.2 g	10
NCD36.G	6418677724183	One inlet, seven outlets, grey	104.2 g	10
NCD36.P	6418677724190	One inlet, seven outlets, red	104.2 g	10



Four-pole T-distributor, two outlets

A plug coupler can be connected to the device with a cable or mounted on the frame of the device with a panel mounting adapter, which is sold separately.

Product code	GTIN	Description	Weight	Package
NAD4T.W	6418677703652	One inlet, two outlets, white	30.2 g	10/50



Four-pole T-distributor, two outlets, a separate locking device on the side branch

The component can be used when the device does not have space for the standard plane mounting adapter. A plug coupler can be connected to the device with a cable or mounted on the frame of the device with a narrow plane mounting adapter, which is sold separately.

Product code	GTIN	Description	Weight	Package
NAD4TH3.W	6418677703669	One inlet, two outlets, white, no locking latches on the side branch	29.4 g	10/50



Five-pole T-distributors, two outlets

A plug coupler can be connected to the device with a cable or mounted on the frame of the device with a panel mounting adapter, which is sold separately.

Product code	GTIN	Description	Weight	Package
NAD5T.W	6418677716645	One inlet, two outlets, white	37.7 g	10/50
NAD5T.B	6418677716652	One inlet, two outlets, black	37.7 g	10/50
NCD5T.G	6418677716669	One inlet, two outlets, grey	37.7 g	10/50
NCD5T.P	6418677716676	One inlet, two outlets, red	37.7 g	10/50



Five-pole Linect T-block, two outlets

Linect T-block with a supply and outlet, specifically designed for DALI-controlled dimming. The T branch is connected to the lighting fixture with a Linect screwless coupler. Linect code I - blue

Product code	GTIN	Description	Weight	Package
NCD5LI.G	6418677724466	Linect T-block, five poles, C/I code (1, N, PE, a+, b-)	71 g	10/50

