

ENSTO

NCC22S.G

Coupler

Code	NCC22S.G
GTIN	6418677117183
ENumber	
Name	Coupler EnstoNet Grey (a+, b-)
Description	For flexible, stranded and solid wires. Wire cross-section 0,75-4,0 mm ² . Strain-relief for cables with outer diameter of 5,5-11,5 mm.
Vendor	Ensto Finland Oy
	



Technical specification

Technical specification

UL Wire range: 12 ... 18 AWG

Dimensions

Weight: 12.3 g

Conductor cross-section: 0,75 - 4 mm²

Dimensions l x w x h: 50x29x20

Temperatures

Max. operating temperature: +70 °C

Min. installation temperature: +5 °C

Min. operating temperature: -30 °C (without mechanical stress)

Materials

Material: Polyamide 66

Colors

Color: Grey

Features

Pole markings: a+,b-

Drawing markings

L: 250 mm

Ratings

Rated voltage: 250 V
Degree of protection: IP20
Flammability rating: UL 94 V-2
Rated current: 20 A
ETIM class: EC002560

US specific

UL Rated voltage: 250 V
UL Rated current: 16 A

ETIM

ETIM

Width: 29 mm
Length: 50 mm
Height: 20 mm
Degree of protection (IP): IP20
Material housing: Polyamide
Nominal rated current: 20 A
Model: Plug
Halogen free: true
Connection type: Screw connection
Number of poles: 2
Nominal rated voltage: 250 V
Strain relief: true
Locking mechanism: Integrated in plug-in connector
Mechanical coding: true
Contact material: CuZn
Connection cross section (solid-core): 0.75 ... 4 mm²
Number of connections per pole: 1
Pollution degree: 2
Colour coding/contact insert: Grey
Max. continuous temperature resistance contact part: 70 °C
Max. continuous temperature resistance strain relief: 70 °C
Surface finish contacts: Silver-plated
Rated surge voltage: 4 kV
Connection cross section (fine-strand): 0.75 ... 4 mm²
Cable diameter: 5 ... 11.5 mm

Packaging

Default package

Unit: PCS

Size: 200

Pallet package

Size: 12600

