

F20 2U Fixed Patch Panel

V.3.3

Description

FibreFab offers an innovative, robust 2U fixed patch panel. This panel has been designed to accept up to 96 fibres housed within a 2U space.

With the ability to use a full array of adaptor types, this panel offers a flexible solution to the end user; enabling them to incorporate a multi functional panel which allows easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to array of adapters the panel also offers multiple cable entry solutions, up to 8 standard entry points for loose tube, tight buffered, pre-terminated and steel tape armoured cable.








Features/Benefits

- ▶ Up to 96 fibres in 2U
- ▶ Multiple adaptor options available
- ▶ 48 adaptor positions
- ▶ Individually labelled ports
- ▶ ROHS, REACH SvHC
- ▶ Fits standard 19"

Applications

- ▶ Data centres, premise installations, telecommunication networks
- ▶ Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- ▶ Data communication
- ▶ Indoor applications



Material: Steel
Finish: Powder Coat



+44 (0) 870 127 3330



+44 (0) 870 127 3331



sales@fibrefab.com



www.fibrefab.com

F20 2U Fixed Patch Panel

Technical Specification

Element	
Height	2U (88.8mm)
Width	480mm
Depth	300mm
Net weight	3.7kg
Packaged weight	3.9kg
Packaged dimensions	530mm (W) x 110mm (H) x 330mm (D)
IP Rating	IP20
Suitable for adaptor type	SC Simplex - LC Duplex - E2000
Number of ports	48
Cable entry 20mm	4
Cable entry 25mm	4
Mounting adjustment range	80mm
Material	Cold rolled steel
Material thickness	1.2mm
Material coating	Powder coating
Colour	Black RAL 9004
Operating temperature	-40°C to + 60°C
Compliant to	RoHS, Reach / SVHC
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN 50173, IEC 60304, IEC 61754, EN 297-1

Part Number Generator

