

Data sheet

ID	KSXS BK
Description	cable ducting
Properties	plain medium resistance against compression, normal impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	flame propagating
Classification	N 450



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Length		Operating temperature		UV-Level
6 m		-30 bis +70 °C		L2
Art. no.	Outer diameter	Inner diameter	Small Package	Large Package
016 818	90 mm	79,4 mm	6 m	828 m
017 091	110 mm	97 mm	6 m	570 m

Further technical details

Details	
Model	Rigid
Shape	Outer - and inner side plain
Surface protection	Untreated
Transparent	False
Material	PE

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.