

Data sheet

ID	HFUM BK
Description	slip type coupler, halogen free
Properties	for the connection of conduits, suitable for rigid and pliable conduits
Colour	black, similar to RAL 9005

Norms: EN 61386



Operating temperature
-25 bis +90 °C

UV-Level
L2

Art. no.	For tube diameter, large	For tube diameter, small	Small Package	Large Package
026 402	25 mm	20 mm	100 pc	800 pc

Further technical details

Details

Surface protection	Untreated
Surface polished	False
Halogen free	True
Material	PC/ABS

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.