


Data sheet

ID	PKGH OP LG
Description	enclosure box, jetting water tight, halogen-free
Properties	for surface installation, suitable for damp locations, without pre-punched conduit entries
Colour	light grey, similar to RAL 7035
Classification	AC 690 V, IP 40

Norms: EN 60670-1, EN 60670-22
halogenfree according to EN 60754



Working temperature		Degree of protection (IP)	UV-Level*	
-25 to +105 °C		IP65	L1	
Art. no.	Dimensions Ø/LxB x T	ps	pl	
023 760	105 x 105 x 64 mm	5 pc	50 pc	
023 761	200 x 150 x 85 mm	2 pc	12 pc	
023 762	300 x 200 x 125 mm	1 pc	4 pc	

Further technical details

Details	
Halogen free	True
Tackable	False
Number of inlets	-
Type of housing feed-through	None
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	False
Weatherproof	False
Material	PC-Blend

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.