


Data sheet

ID	PKG MP BK
Description	enclosure box, jetting water tight
Properties	for surface installation, suitable for damp locations, with pre-punched conduit entries
Colour	black, similar to RAL 9005
Classification	AC 690 V, IP 40

Norms: ÖVE/ÖNORM EN 60670-22:2007



Working temperature		Degree of protection (IP)	UV-Level	
-25 to +60 °C		IP65	L2	
Art. no.	Dimensions Ø/LxB x T	For tube diameter	Small Package	Large Package
016 404	105 x 105 x 64 mm	25 mm	5 pc	50 pc
010 789	200 x 150 x 85 mm	25 mm	2 pc	12 pc

Further technical details

Details

Halogen free	False
Tackable	False
Number of inlets	6
Type of housing feed-through	Preembossing
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	False
Weatherproof	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.