Data sheet



HFCB xx/3-Y BK M4 ID

Description distribution box, halogen-free

Properties Circular box for surface installation with 2 mounting

> lugs, standard mounting screw spacing 50.8mm (2") for conduit diameters 20 mm, 25 mm oder 32

mm, with brass inserts M 4, without lid

Colour black, similar to RAL 9005


IP30 Classification











Working temperature	Degree of protection (IP)	UV-Level*
-25 to 90 °C	IP3X	L2

Art. no.	Dimensions Ø/LxB x T	For tube diameter	ps	pl
097 987	65 x 32 mm	20 mm	20 pc	160 pc
097 989	65 x 32 mm	25 mm	20 pc	160 pc

Further technical details

Details				
Halogen free	True			
Tackable	False			
Number of inlets	3			
Type of housing feed-through	Pipe socket			
Equipped with	None			
Cover model	Mounting cover			
Explosion-tested version	False			
Weatherproof	False			
Material	PC-Blend			

^{*)} L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.