

# Data sheet

ID	<b>QK WH</b>
Description	cover joint
Properties	for Starline-trunking SLQ
Colour	white, similar to RAL 9010
Fire Behaviour	non flame propagating



UV-Level

L2

Art. no.	For wall duct width	Small Package	Large Package
036 072	170 mm	10 pc	200 pc
086 026	250 mm	5 pc	100 pc

## Further technical details

### Details

Model	Duct joint cover
Shape	Symmetric
Type of fastening	Snap on
Halogen free	False
Surface protection	Untreated
Material	PVC-U

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, [www.dietzel-univolt.com](http://www.dietzel-univolt.com), makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.