

Data sheet

ID	FUM BK
Description	slip type coupler
Properties	for the connection of pliable and rigid ducting systems
Colour	black, similar to RAL 9005



Operating temperature			UV-Level	
-5 bis +60 °C			L2	
Art. no.	For tube diameter, large	For tube diameter, small	Small Package	Large Package
002 002	65 mm	63 mm	60 pc	-
002 003	80 mm	75 mm	35 pc	-
002 004	100 mm	90 mm	22 pc	-
002 005	110 mm	100 mm	18 pc	-
002 008	160 mm	140 mm	4 pc	-
002 009	160 mm	160 mm	3 pc	-

Further technical details

Details

Surface protection	Untreated
Surface polished	False
Halogen free	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.