


IC: 50K00C

TYPE: ОКТ-Д(1,0)Пнг-НН

J/A-DQ(BN)H WBF max.12 fibers

Application: this cable is suitable for indoor or outdoor installation.

Construction



Fiber color coding

According to IEC 60304

1 Red	7 Brown
2 Green	8 Violet
3 Blue	9 Turquoise
4 Yellow	10 Black
5 White	11 Orange
6 Grey	12 Pink

Order example

2000 m J/A-DQ(ZN)H 12E9/125G.652D WBF BLK jacket color, identification code: 50K00C

Packaging

Plywood reel or wooden drum

Standart put-up length

2000 m

Sheat Marking

Print colour	White
Print method	INK-Jet
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

IES reserves the right to change the values in this document without prior notice. This document is property of company IES. This document or any of its parts are not allowed to be redistributed without written consent of company IES.

Mechanical and Environmental properties

Optical	
Type of fiber optic	
Single mode fiber 9/125	
Multi mode fiber 50/125	
Multi mode fiber 62,5/125	
Test	Value
Cable outer diameter	6.0 mm \pm 0.400
Cable weight	30.020 kg/km
Loose tube diameter	2,5 mm
Short tern	1000 N
Impact resistance test	3 Number of. impact
Min. bend radius (no load)	120
Min. bend radius (load)	160
Operating temperature, °C	-40°C - +60°C
Storage temperature, °C	-40°C - +60°C
Installation temperature, °C	-10°C - +60°C
Cable life time- minimum 20 years	