


IC: XX1094

TYPE: ОКАДТ-Д(2,5)П-2*3,5

A-D(ZN)2YT 2×3,5 max. 48 fibers

Application: this cable is suitable for indoor or outdoor aerial use.

Construction



Fiber color coding

According to IEC 60304

1 Red	7 Brown	13 Red*	19 Brown*
2 Green	8 Violet	14 Green*	20 Violet*
3 Blue	9 Turquoise	15 Blue*	21 Turquoise*
4 Yellow	10 Black	16 Yellow*	22 Black*
5 White	11 Orange	17 White*	23 Orange*
6 Grey	12 Pink	18 Grey*	24 Pink*

* s čiernym pásikom

Order example

2000 m A-DQ(2ZN)2Y 2X24E9/125 G.652D BLK jacket color, identification code: XX1094

Packaging

Plywood reel or wooden drum

Standart put-up length

2000 m

Sheat Marking

Print colour	White
Print method	INK-Jet
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

IES reserves the right to change the values in this document without prior notice. This document is property of company IES. This document or any of its parts are not allowed to be redistributed without written consent of company IES.

Mechanical and Environmental properties

Optical	
Type of fiber optic Single mode fiber 9/125 Multi mode fiber 50/125 Multi mode fiber 62,5/125	
Test	Value
Cable outer diameter	11.6 x 5 mm
Cable weight	60.911kg/km
Loose tube diameter	3,5 mm
Short tern	2500 N
Impact resistance test	3 Number of. impact
Min. bend radius (no load)	120
Min. bend radius (load)	160
Operating temperature, °C	-40°C - +60°C
Storage temperature, °C	-40°C - +60°C
Installation temperature, °C	-10°C - +60°C
Cable life time- minimum 20 years	

IES reserves the right to change the values in this document without prior notice. This document is property of company IES. This document or any of its parts are not allowed to be redistributed without written consent of company IES.