


IC: XX0042

TYPE: ОКАД-ММ(1,0)ПНГ-НФ-89642202-2

FLAT AERIAL DROP 2E9/125 G657A

Application: this cable is suitable for FTTx aerial installation

Construction



Fiber color coding

According to IEC 60304

1 Red

2 Green

Order example

2000 m FLAT AERIAL DROP 2E9/125 G657A BLK jacket color, identification code: XX0042

Packaging

Plywood reel or wooden drum

Standart put-up length

2000 m

Sheat Marking

Print colour

White

Print method

INK-Jet

Print legend

Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

IES reserves the right to change the values in this document without prior notice. This document is property of company IES. This document or any of its parts are not allowed to be redistributed without written consent of company IES.

83104 Bratislava, Nová Rožňavská 136

E-mail: ies@ies.sk

www.ies.sk

Mechanical and Environmental properties

Optical	
Type of fiber optic Single mode fiber 9/125 Multi mode fiber 50/125 Multi mode fiber 62,5/125	
Test	Value
Cable outer diameter	5,0x2,0 mm
Cable weight	19.385 kg/km
Short tern	1000 N
Impact resistance test	3 Number of. impact
Min. bend radius (no load)	120
Min. bend radius (load)	160
Operating temperature, °C	-40°C - +60°C
Storage temperature, °C	-40°C - +60°C
Installation temperature, °C	-10°C - +60°C
Cable life time- minimum 20 years	

IES reserves the right to change the values in this document without prior notice. This document is property of company IES. This document or any of its parts are not allowed to be redistributed without written consent of company IES.