

Product information HiVision 6.3 HPUX Enterprise-Update

Name	HiVision 6.3 HPUX Enterprise-Update
	A PROVIDE AND A PROVIDA AND A
)olivory informations	Network management software license
Delivery informations Availability	no longer available
Product description	ווט וטווער מימוומטוכ
Description	Network management software license
Гуре	HiVision 6.3 HPUX Enterprise-Update
Drder No.	943 471-405
Configuration	
Configuration functions	- autodiscovery of all ICMP and SNMP devices.
	- save devices in a devicelist
	- export of all tables to ASCII files
	- import of Product-Specific Modules. Users can build their own
	modules for unknown devices.
	additional support: Competence Center Value Added Products
	- multi-device-configuration: multiple configuration of devices, e.g. software update
	- multi-port-manager: multiple configuration of ports from different devices.
	- configuration of all Hirschmann components including network wide VLANs
	and user groups.
	- trap history for whole network and single devices.
	- satus propagation seperately configurable for device, card,
	port, power supplies, fans & chassis.
	- configuration of RMON Alarms and Events
	- integrated SNMP MIB Browser
	- easy Configuration of MACH 3000 Router Redundancy
Diagnostics	
Diagnostic functions	- monitoring of ICMP- and SNMP devices
	- detailled view of devices health
	- alarm and event protocol including definition of event-actions
	like messagebox, eMail, SMS or start of any program
	- configurable status configuration
	- multi-port-analyzer for network wide port diagnostic and utilization control
	- assignment of MAC-Address to IP-Address, to seek MAC
	- integrated OPC Server HiControl in Windows Version, thereby easy integration in SCADA applications of device status and
	the reason for status change
	- long-run monitoring with SNMP monitor include log function
Aodules and supported components	
Aodules and components	MACH 4000, MACH 3000, LION, GigaLION, SmartLION, EAGLE
	Foundry Networks Fastlron series
Software requirements	
Operating system	HPUX 11.0
Stand-alone / integrated HP OpenView - v	
Minimum requirement for Hirschmann ag	
Browser	e.g. Netscape 4.7 or higher
	java runtime environment on CD





Industrial Ethernet:Archive - Industrial Ethernet:Network Management (Archive):HiVision:HiVision 6.3 HPUX Enterprise-Update		
http://e-catalog.hirschmann.com/link/57078-24455-49814-103324-24542-34289/en/conf/uistate		
Hardware requirements		
Processor	x86 compatible CPU, recommended > 500 MHZ	
RAM	at least 128MB, 256 MB (recommended)	
	HiVision requires approximately 50 MB free RAM. A further 200 kB of RAM are required for each detected agent. The network management unit also requires	
	RAM for the operating system and any additional applications such as OpenView.	
Hard disk space	80 MB free	
Recommended resolution	1024 x 768	
Network	ETHERNET network with TCP/IP protocol stack	
Scope of delivery and accessories		
Scope of delivery	printed manual (German and English)	
	fax form for licensing	
	CD-ROM with multilingual product version	
	online documentation, testversions Industrial HiVision, HiOPC	
	Acrobat reader and java runtime environment	
Product variants		
Version + Nodes	update	

For more information please contact: Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51 72654 Neckartenzlingen Germany Phone: +49 7127/14-1809 E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

