

**3094A Coax - ControlBus™ Quad Shielded Coax**

For more Information
please call

1-800-Belden1

**Description:**

14 AWG solid bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® IV quad shield (100% coverage), PVC Jacket.

Usage (Overall)

Suitable Applications: RG-11/U Type

Physical Characteristics (Overall)**Conductor**

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	14	Solid	BCCS - Bare Copper Covered Steel	1.6256

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected FPE - Foam Polyethylene	7.112

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	AL - Aluminum	60
3	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
4		Braid	AL - Aluminum	40

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 10.338 mm

Mechanical Characteristics (Overall)

Operating Temperature Range:	-30°C To +80°C
Bulk Cable Weight:	87.804 Kg/Km
Max. Recommended Pulling Tension:	1370.046 N
Min. Bend Radius/Minor Axis:	114.300 mm

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CL2R, CMR
CEC/C(UL) Specification:	CMG
EU Directive 2000/53/EC (ELV):	Yes

3094A Coax - ControlBus™ Quad Shielded Coax

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: 11/U

Flame Test

UL Flame Test: UL1666 Riser

CSA Flame Test: FT4

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 3095A

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)	Tolerance (Ohms)
75	± 3

Nom. Inductance:

Inductance (µH/m)
0.318257

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
53.1522

Nominal Velocity of Propagation:

VP (%)
82

Nominal Delay:

Delay (ns/m)
3.9372

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
36.091

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
4.9215

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	0.52496
2	0.59058
5	0.85306
10	1.24678
20	1.80455
50	2.72323
100	3.83877
200	5.2496
300	6.52919
400	7.5463

Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
-------------	-----------------------

3094A Coax - ControlBus™ Quad Shielded Coax

1	1.08273
2	1.14835
5	1.44364
10	2.16546
20	2.55918
50	3.24819
100	4.33092
200	6.13547
300	7.51349
400	8.66184

Max. Operating Voltage - UL:

Voltage
300 V RMS

Minimum Structural Return Loss:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. SRL (dB)
		5	400	20

Notes (Overall)

Notes: Sweep tested 5 to 400 MHz. Tap marks every 2.6 Meters to aid users in installation.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3094A F2V1000	305 MT	30.391 KG	GRAY, DEC		#14 GIFHDLDPD DSH PVC
3094A F2V2000	610 MT	61.689 KG	GRAY, DEC	C	#14 GIFHDLDPD DSH PVC
3094A F2V500	152 MT	15.649 KG	GRAY, DEC		#14 GIFHDLDPD DSH PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 06-13-2012

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.