

Insulated Spacer Beams

insulated spacer beams made of fibreglass Ø 16 mm, for maintaining separation distances

IDH16/BPL, insulated spacer beam with mounting bracket; for installation of interception rods Ø 16 mm or round wires Ø 6–11 mm



item code	material	for Ø [mm]	ins. dist. [mm]	pieces	ref.
IDH750-16/16Niro/BPL AI	GFI/V2A/AI	16	600	1	084 893
IDH1000-16/16Niro/BPL AI	GFI/V2A/AI	16	800	1	084 894
IDH1200-16/16Niro/BPL AI	GFI/V2A/AI	16	1000	1	084 895
IDH750-16/6-11Niro/BPL AI	GFI/V2A/AI	6-11	600	1	084 896
IDH1000-16/6-11Niro/BPL AI	GFI/V2A/AI	6-11	800	1	084 897
IDH1200-16/6-11Niro/BPL AI	GFI/V2A/AI	6-11	1000	1	084 898

IDH16/BPS, insulated spacer beam with plate for lateral mounting; for installation of interception rods Ø 16 mm or round wires Ø 6–11 mm



item code	material	for Ø [mm]	ins. dist. [mm]	pieces	ref.
IDH750-16/16Niro/BPS Niro	GFI/V2A	16	600	1	084 899
IDH1000-16/16Niro/BPS Niro	GFI/V2A	16	800	1	084 900
IDH1200-16/16Niro/BPS Niro	GFI/V2A	16	1000	1	084 901
IDH750-16/6-11Niro/BPS Niro	GFI/V2A	6-11	600	1	084 902
IDH1000-16/6-11Niro/BPS Niro	GFI/V2A	6-11	800	1	084 903
IDH1200-16/6-11Niro/BPS Niro	GFI/V2A	6-11	1000	1	084 904