

**BS**, concrete base; for fixing 8mm round wires on flat roofs, frost resistant



| item code     | material   | dn [mm]    | weight [kg] | pieces | ref.           |
|---------------|------------|------------|-------------|--------|----------------|
| BS-recyclable | concrete   | 175x128x73 | 1           | 1      | <b>081 904</b> |
| BS-concrete   | K/concrete |            | 1           | 1      | <b>063 934</b> |

**UL**, cleat; for 8 mm round wires



| item code   | material | spec.             | clp. r/r [mm] | ps [pcs] | ref.           |
|-------------|----------|-------------------|---------------|----------|----------------|
| UL8-10/28fv | fv       | hole spacing 28mm | 8-10          | 500      | <b>006 209</b> |
| UL8-10/28Cu | Cu       | hole spacing 28mm | 8-10          | 500      | <b>006 564</b> |
| UL16/38fv   | fv       | hole spacing 38mm | 16            | 500      | <b>006 211</b> |

**VS/UL**, twist protection cleat; for 8 mm round wires



| item code | material | clp. r/r [mm] | ps [pcs] | ref.           |
|-----------|----------|---------------|----------|----------------|
| VS/ULNiro | V2A      | 6-8           | 100      | <b>063 872</b> |
| VS/ULCu   | Cu       | 6-8           | 100      | <b>063 871</b> |

**DDF**, roof bushing; for sealing of roofs at down conductor lead-in, for tiled and corrugated sheet roofs (drilling hole Ø 16mm)



| item code | material | spec.                 | for Ø [mm] | ps [pcs] | ref.           |
|-----------|----------|-----------------------|------------|----------|----------------|
| DDF/K8-10 | K        | ø34mm, bore hole 16mm | 8-10       | 25       | <b>064 821</b> |