


Locknuts, metric

Gegenmuttern, metrisch



Temperature range: -40°C to 100°C, interm. up to approx. 150°C
Material: Polyamide / reinforced glass fibre

Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis ca. 150°C
Material: Polyamid / glasfaserverstärkt

Type	WISKA-No. RAL 7035 □	WISKA-No. RAL 9005 ■	WISKA-No. RAL 7001 ■		 mm	 mm	TL mm
EMUG 12	10060770	10061780	10062712	100/1000	M 12x1,5	18	5
EMUG 16	10060771	10061781	10062713	100/1000	M 16x1,5	22	5
EMUG 20	10060772	10061782	10062714	100/1000	M 20x1,5	27	5
EMUG 25	10060773	10061783	10062715	100	M 25x1,5	32	6
EMUG 32	10060774	10061784	10062716	100	M 32x1,5	40	6
EMUG 40	10060775	10061785	10062717	50	M 40x1,5	50	7
EMUG 50	10060776	10061786	10062718	25	M 50x1,5	60	7
EMUG 63	10060777	10061787	10062719	10	M 63x1,5	75	7

Locknuts, PG

Gegenmuttern, PG

Type	WISKA-No. RAL 7035 □	WISKA-No. RAL 9005 ■		 mm	 mm	TL mm
MUG 7	10060670	10060680	100/1000	PG 7	19	5
MUG 9	10060671	10060681	100/1000	PG 9	22	5
MUG 11	10060672	10060682	100/1000	PG 11	24	5
MUG 13,5	10060673	10060683	100/1000	PG 13,5	27	6
MUG 16	10060674	10060684	100/1000	PG 16	30	6
MUG 21	10060675	10060685	100/1000	PG 21	36	7
MUG 29	10060676	10060686	50	PG 29	46	7
MUG 36	10060677	10060687	25	PG 36	60	8
MUG 42	10060678	10060688	25	PG 42	65	8
MUG 48	10060679	10060689	10	PG 48	70	8

KUNSTSTOFF PLASTIC
 MEMBRAN MEMBRANE
 MESSING BRASS
 DIN 89280
 EDELSTAHL STAINL. STEEL
 EMV EMC
 ATEX
 VentGLAND
 BS 6121
 DICHTUNGEN SEALINGS
 WERKZEUGE TOOLS
 TECHNIK TECHNICS
 INDEX INDEX