


QUIXX Membrane spouts, two-component cable entry




Protection class to EN 60 529: IP 66
Temperature range: -40°C to 80°C, interm. up to approx. 100°C
Material: Polyethylene / Thermoplastic elastomere
Equipment: - Dust tight, quick and easy mounting
 - Also available for tightening of special cables
 - For enclosures with more than 2 mm wall thickness

Schutzart gemäß EN 60 529: IP 66
Einsatztemperatur: -40°C bis 80°C, kurzzeitig bis ca. 100°C
Material: Polyethylen / Thermoplastisches Elastomer
Ausstattung: Staubdicht, montagefreundlich
 - Auch für die Abdichtung von Sonderkabeln geeignet
 - Zur Verwendung in Gehäusen mit Wandstärken ab 2 mm

Type	WISKA-No. RAL 7035					TL	
			mm	mm	mm	mm	mm
EMT 16	10062559	100	16	9,5	1 · 9	11	16,5
EMT 20	10062560	100	20	9,5	1 · 13	11	20,5
EMT 25	10062561	100	25	9,5	1 · 18	11	25,5
EMT 32	10062562	100	32	9,5	1 · 25	11	32,5

QUIXX Membrane spouts, two-component cable entry, flame-retardant



Protection class to EN 60 529: IP 66
Temperature range: -40°C to 80°C, interm. up to approx. 100°C
Material: Polyethylene, flame-retardant / Thermoplastic elastomere
Equipment: - Flame-safe acc. to UL 94 V2
 - Colour cream white, similar to RAL 9001
 - Dust tight, quick and easy mounting
 - Also available for tightening of special cables
 - For enclosures with more than 2 mm wall thickness

Schutzart gemäß EN 60 529: IP 66
Einsatztemperatur: -40°C bis 80°C, kurzzeitig bis ca. 100°C
Material: Polyethylen, flammwidrig / Thermoplastisches Elastomer
Ausstattung: - Flammschutz nach UL 94 V2
 - Farbe cremeweiß, ähnlich RAL 9001
 - Staubdicht, montagefreundlich
 - Auch für die Abdichtung von Sonderkabeln geeignet
 - Zur Verwendung in Gehäusen mit Wandstärken ab 2 mm

Type	WISKA-No.					TL	
			mm	mm	mm	mm	mm
EMT-F 16	10063008	100	16	9,5	1 · 9	11	16,5
EMT-F 20	10063009	100	20	9,5	1 · 13	11	20,5
EMT-F 25	10063010	100	25	9,5	1 · 18	11	25,5
EMT-F 32	10063011	100	32	9,5	1 · 25	11	32,5