

QUIXX Membrane screws, two-component cable entry, metric



Protection class to EN 60 529: IP 66

Temperature range: -30°C to 80°C, interm. up to approx. 100°C


Material: Polypropylene / Thermoplastic elastomere

Equipment: Dust tight, quick and easy mounting

- Also available for tightening of special cables

- For applications with threaded holes or fixing with locknut

Variations: Other colours on request



Schutzart gemäß EN 60 529: IP 66

Einsatztemperatur: -30°C bis 80°C, kurzzeitig bis ca. 100°C

Material: Polypropylen / Thermoplastisches Elastomer

Ausstattung: Staubdicht, montagefreundlich

- Auch für die Abdichtung von Sonderkabeln geeignet

- Zur Verwendung mit Gegenmutter oder in vorhandenen Gewinden

Varianten: Andere Farben auf Anfrage

Type	WISKA-No. RAL 7035						TL
			mm	mm	mm	mm	mm
EMS 16	10062567	100	M 16x1,5	9	1 · 9	17	15
EMS 20	10062568	100	M 20x1,5	9	1 · 13	20	15
EMS 25	10062569	100	M 25x1,5	9	1 · 18	24	15
EMS 32	10062570	100	M 32x1,5	9	1 · 25	32	15

KUNSTSTOFF
PLASTIC

MEMBRAN
MEMBRANE

MESSING
BRASS

DIN 89280

EDELSTAHL
STAINL. STEEL

EMV
EMC

ATEX

VertGLAND

BS 6121

DICHTUNGEN
SEALINGS

WERKZEUGE
TOOLS

TECHNIK
TECHNICS

INDEX
INDEX