

## SPRINT ATEX cable glands Low Temp. metric

## SPRINT ATEX Kabelverschraubungen LowTemp, metrisch



**Explosion protection:** II 2 G Ex e II

II 2 D Ex tD A21 IP68

**Certificates:** PTB 04 ATEX 1112 X

**Protection class to EN 60 529:** IP 68 to 5 bar (30 min)

**Protection class to DIN 40 050-T9:** IP 69K

**Temperature range:** -60°C to 75°C

**Material:** - Cable gland: brass nickel-plated

- Clamping cage: polyamide

- Gasket: silicone


**Equipment:** - Maximum traction relief through WISKA patent lamella

- Seal-tight to enclosure rack through additional silicone O-ring

- Same sealing range and key width on all SPRINT-glands

- Available with reduction insert,

- Available dust-protection gasket



**Explosionsschutz:** II 2 G Ex e II

II 2 D Ex tD A21 IP68

**Bescheinigungen:** PTB 04 ATEX 1112 X

**Schutzart gemäß EN 60 529:** IP 68 bis 5 bar (30 min)

**Schutzart gemäß DIN 40 050-T9:** IP 69K

**Einsatztemperatur:** -60°C bis 75°C

**Material:** - Verschraubung: Messing vernickelt

- Klemmkäfig: Polyamid

- Dichtung: Silikon

**Ausstattung:** - Optimale Abdichtung und Zugentlastung durch

patentiertes WISKA-Lamellensystem

- Abdichtung am Gehäuse durch zusätzlichen Silikon O-Ring

- Gleiche Dichtbereiche und Schlüsselweiten für alle SPRINT-

Verschraubungen

- Lieferbar mit Reduzierdichteinsatz

- Lieferung mit Staubschutzscheibe

Type	WISKA-No. Ni					TL	
			mm	mm	mm	mm	
EMSKE 12 LT	10065946	50	M 12x1,5	5	4 · 7	16	23 · 30
EMSKE 16 LT	10065947	50	M 16x1,5	5	5 · 10	20	26 · 34
EMSKE 20 LT	10065948	50	M 20x1,5	6	6 · 13	24	29 · 37
EMSKE 25 LT	10065949	50	M 25x1,5	7	10 · 17	29	33 · 42
EMSKE 32 LT	10065950	25	M 32x1,5	8	13 · 21	36	36 · 44
EMSKE 40 LT	10065951	10	M 40x1,5	8	16 · 28	46	44 · 55
EMSKE 50 LT	10065952	10	M 50x1,5	9	21 · 35	55	51 · 62
EMSKE 63 LT	10065953	10	M 63x1,5	10	34 · 48	68	56 · 67

**Recommended accessories:**

Empfohlenes Zubehör:



EMMU

Page / Seite 64

KUNSTSTOFF  
PLASTIC

MEMBRAN  
MEMBRANE

MESSING  
BRASS

DIN 89280

EDELSTAHL  
STAINL. STEEL

EMV  
EMC

ATEX

Vertigland

BS 6121

DICHTUNGEN  
SEALINGS

WERKZEUGE  
TOOLS

TECHNIK  
TECHNICS

INDEX  
INDEX