


SPRINT EX cable glands, ESKE/1-e, for increased safety, polyamide, metric



ESKE/1-e



ESKE/1-L-e



Marking: II 2 G Ex e IIC Gb
I 2 D Ex tb IIIC Db IP68

Approval: IECEx PTB 13.0034X
PTB 13 ATEX 1015X

Protection class: IP 66 / IP 68, 5 bar 30 min

Glow wire test: 750 °C

Temperature range: -40 °C · 75 °C

Material: Gland: Polyamide, Gasket: EPDM

ESKE/1-e

Type	WISKA-No. RAL 9005					TL (mm)	
ESKE/1-e 12	10103363	M 12x1,5	9	3 · 6	16	29 · 34	50
ESKE/1-e 16	10103364	M 16x1,5	9	4,5 · 9	20	31 · 37	50
ESKE/1-e 20	10103365	M 20x1,5	10	7 · 13	24	36 · 45	50
ESKE/1-e 25	10103366	M 25x1,5	10	10 · 17	29	38 · 47	50
ESKE/1-e 32	10103367	M 32x1,5	12	13 · 21	36	42 · 51	25
ESKE/1-e 40	10103368	M 40x1,5	12	17 · 28	46	52 · 65	10
ESKE/1-e 50	10103369	M 50x1,5	14	23 · 35	55	59 · 72	4
ESKE/1-e 63	10103370	M 63x1,5	15	34 · 48	68	64 · 78	1

ESKE/1-L-e, long

Type	WISKA-No. RAL 9005					TL (mm)	
ESKE/1-L-e 12	10103379	M 12x1,5	15	3 · 6	16	35 · 40	50
ESKE/1-L-e 16	10103380	M 16x1,5	15	4,5 · 9	20	37 · 43	50
ESKE/1-L-e 20	10103381	M 20x1,5	15	7 · 13	24	41 · 48	50
ESKE/1-L-e 25	10103382	M 25x1,5	15	10 · 17	29	43 · 51	50
ESKE/1-L-e 32	10103383	M 32x1,5	15	13 · 21	36	45 · 53	25
ESKE/1-L-e 40	10103384	M 40x1,5	18	17 · 28	46	58 · 71	10
ESKE/1-L-e 50	10103385	M 50x1,5	18	23 · 35	55	63 · 76	4
ESKE/1-L-e 63	10103386	M 63x1,5	18	34 · 48	68	67 · 81	1

Recommended accessories

