


Cable glands, metric, hexagonal

Kabelverschraubungen, metrisch, 6-Kant



Protection class to EN 60 529: IP 54, installation with connection thread gasket IP 66

Temperature range: -25°C to 80°C, interm. up to approx. 100°C

Material: - Cable gland: brass nickel-plated

- Gasket: soft rubber

Equipment: - Low-priced brass gland for round cable for mounting with spanner

- Connection and functional thread metric

- With universal gasket

Schutzart gemäß EN 60 529: IP 54; bei Montage mit Anschlussgewindedichtring IP 66

Einsatztemperatur: -25°C bis 80°C, kurzzeitig bis ca. 100°C






Material: - Verschraubung: Messing vernickelt

- Dichtung: Weichgummi

Ausstattung: - Preisgünstige Messing-Kabelverschraubung für Rundkabel zur Montage mit Gabelschlüssel

- Anschlussgewinde und Funktionsgewinde metrisch

- Mit ausschneidbarem Dichtring

Type	WISKA-No. Nr.						TL
			mm	mm	mm	mm	mm
ESMKV 12	10062870	100	M 12x1,5	4 · 6	12	14	20
ESMKV 16	10062871	100	M 16x1,5	2 · 10	16	18	22
ESMKV 20	10062872	50	M 20x1,5	3 · 14	18	22	26
ESMKV 25	10062873	50	M 25x1,5	7,5 · 18	25	27	29
ESMKV 32	10062874	25	M 32x1,5	15 · 25	32	34	32
ESMKV 40	10062875	20	M 40x1,5	22 · 33	40	42	38
ESMKV 50	10062876	5	M 50x1,5	31 · 42	52	50	48
ESMKV 63	10062877	5	M 63x1,5	40 · 51	63	66	46

Cable glands, PG, hexagonal

Kabelverschraubungen, PG, 6-Kant

Type	WISKA-No. Nr.						TL
			mm	mm	mm	mm	mm
SMKV 7	10062061	100	PG 7	5 · 7	13	14	20,5
SMKV 9	10062082	100	PG 9	4 · 11	15	17	22
SMKV 11	10062083	50	PG 11	6,5 · 13,5	18	20	24
SMKV 13,5	10062084	50	PG 13,5	6,5 · 13,5	20	22	26
SMKV 16	10062085	50	PG 16	6,5 · 16	22	24	26,5
SMKV 21	10062086	50	PG 21	9 · 20	28	30	30
SMKV 29	10062087	25	PG 29	17 · 28	37	39	32
SMKV 36	10062088	10	PG 36	23 · 34	47	50	39
SMKV 42	10062089	10	PG 42	29 · 40	54	57	44
SMKV 48	10062090	10	PG 48	35 · 46	50	64	45