

SPRINT multiple sealing inserts

SPRINT Mehrfachdichtungen



Protection class to EN 60 529: IP 66
Temperature range: -40°C to 100°C, interm. up to approx. 120°C
Material: Thermoplastic elastomer
Colour: Black, like RAL 9005
Equipment: - For several single cables to pass through
 - Suitable for all SPRINT glands (polyamide, brass, stainless steel)
Variations: - Other designs on request
 - Special sealing inserts possible



Schutzart gemäß EN 60 529: IP 66
Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis ca. 120°C
Material: Thermoplastisches Elastomer
Farbe: Schwarz, ähnlich RAL 9005
Ausstattung: - Für den Einsatz mehrerer Leitungen in einer Verschraubung
 - Für alle SPRINT-Verschraubungen (Polyamid, Messing, Edelstahl)
Varianten: - Weitere Typen auf Anfrage
 - Sonderdichteinsätze möglich

Type	WISKA-No. black / schwarz			n	
mm					
MFD 12/02/020	10100525	25/250	1 · 2	2	SPRINT 12
MFD 12/04/020	10064392	25/250	0 · 2,0	4	SPRINT 12
MFD 16/02/040	10064393	25/250	2,0 · 4,0	2	SPRINT 16
MFD 16/03/021	10101014	25/250	1 · 2,1	3	SPRINT 16
MFD 20/02/050	10101015	25/250	4 · 5	2	SPRINT 20
MFD 20/02/060	10064395	25/250	4,0 · 6,0	2	SPRINT 20
MFD 20/02/065	10060953	25/250	5 · 6,5	2	SPRINT 20
MFD 20/03/040	10064341	25/250	2,5 · 4,0	3	SPRINT 20
MFD 25/01/065	10060954	25/250	4 · 6,5	1	SPRINT 25
MFD 25/01/090	10101016	25/250	7 · 9	1	SPRINT 25
MFD 25/01/105-01/055	10101255	25/250	5 · 10,5	2	SPRINT 25
MFD 25/02/060	10060452	25/250	4 · 6	2	SPRINT 25
MFD 25/02/070	10063995	25/250	5 · 7	2	SPRINT 25
MFD 25/02/080	10060952	25/250	6 · 8	2	SPRINT 25
MFD 25/03/070	10064342	25/250	5,0 · 7,0	3	SPRINT 25
MFD 25/04/060	10064343	25/250	4,0 · 6,0	4	SPRINT 25
MFD 32/01/115-01/085	10101256	25/250	8 · 11,5	2	SPRINT 32
MFD 32/03/080	10101018	25/250	6 · 8	3	SPRINT 32
MFD 32/04/070	10064344	25/250	5,0 · 7,0	4	SPRINT 32
MFD 32/05/070	10101140	25/250	5,0 · 7,0	5	SPRINT 32
MFD 32/04/080	10064950	25/250	6 · 8	4	SPRINT 32
MFD 32/06/060	10064345	25/250	5,0 · 6,0	6	SPRINT 32
MFD 40/04/100	10101017	25/250	8 · 10	4	SPRINT 40
MFD 40/07/070	10064348	25/250	5,0 · 7,0	7	SPRINT 40

KUNSTSTOFF
PLASTIC

MEMBRAN
MEMBRANE

MESSING
BRASS

DIN 89280

EDELSTAHL
STAINL. STEEL

EMV
EMC

ATEX

Vert.GLAND

BS 6121

DICHTUNGEN
SEALINGS





WERKZEUGE
TOOLS

TECHNIK
TECHNICS

INDEX
INDEX

SPRINT multiple sealing inserts

SPRINT Mehrfachdichtungen

Type	WISKA-No. <small>black / schwarz</small>		 mm		
MFD 40/07/080	10064347	25/250	6 · 8	7	SPRINT 40
MFD 40/08/060	10064346	25/250	5,0 · 6,0	8	SPRINT 40
MFD 40/09/069	10101427	25/250	6 · 7	9	SPRINT 40
MFD 50/09/080	10064394	25/250	6,0 · 8,0	9	SPRINT 50
MFD 50/25/050	10063102	25/250	4 · 5	25	SPRINT 50
MFD 63/01/131-01/118-03/084-02/064	10101114	25/250	6 · 13	7	SPRINT 63
MFD 63/02/065-01/090	10101223	25/250	5 · 9	3	SPRINT 63
MFD 63/03/065	10101201	25/250	5 · 6,5	3	SPRINT 63

KUNSTSTOFF
PLASTIC

MEMBRAN
MEMBRANE

MESSING
BRASS

DIN 89280

EDELSTAHL
STAINL. STEEL

EMV
EMC

ATEX

VentGLAND

BS 6121

DICHTUNGEN
SEALINGS

WERKZEUGE
TOOLS

TECHNIK
TECHNICS

INDEX
INDEX