


SPRINT cable glands with locknut, metric

SPRINT Kabelverschraubungen mit Gegenmutter, metrisch



Protection class to EN 60 529: IP 68 to 5 bar (30 min)
Protection class to DIN 40 050-T9: IP 69K
Temperature range: -40°C to 100°C, interm. up to approx. 120°C
Material: - Cable gland and locknut: brass nickel-plated
 - Clamping cage: polyamide
 - Gasket: EPDM
Equipment: - EMSKV with locknut EMMU



Schutzart gemäß EN 60 529: IP 68 bis 5 bar (30 min)
Schutzart gemäß DIN 40 050-T9: IP 69K
Einsatztemperatur: -40°C bis 100°C, kurzzeitig bis ca. 120°C
Material: - Verschraubung und Gegenmutter: Messing vernickelt
 - Klemmkäfig: Polyamid
 - Dichtung: EPDM
Ausstattung: - EMSKV mit Gegenmutter EMMU

Type	WISKA-No. Ni						TL
			D			SW	
			mm	mm	mm	mm	mm
EMSKV-SET 12	10065032	50	M 12x1,5	5	3 - 7	16	23 - 30
EMSKV-SET 16	10065033	50	M 16x1,5	5	4,5 - 10	20	26 - 34
EMSKV-SET 20	10065034	50	M 20x1,5	6	6 - 13	24	29 - 37
EMSKV-SET 25	10065035	50	M 25x1,5	7	9 - 17	29	33 - 42
EMSKV-SET 32	10065036	25	M 32x1,5	8	13 - 21	36	36 - 44
EMSKV-SET 40	10065037	10	M 40x1,5	8	16 - 28	46	44 - 55
EMSKV-SET 50	10065038	10	M 50x1,5	9	21 - 35	55	51 - 62
EMSKV-SET 63	10065039	10	M 63x1,5	10	34 - 48	68	56 - 67

Recommended accessories:
 Empfohlenes Zubehör:



MFD
[Page / Seite 201/202](#)



BS
[Page / Seite 204](#)



RDE
[Page / Seite 198](#)

KUNSTSTOFF
 PLASTIC

MEMBRAN
 MEMBRANE

MESSING
 BRASS

DIN 89280

EDELSTAHL
 STAINL. STEEL

EMV
 EMC

ATEX

VertGLAND

BS 6121

DICHTUNGEN
 SEALINGS

WERKZEUGE
 TOOLS

TECHNIK
 TECHNICS

INDEX
 INDEX