


ATEX stop ends, metric

ATEX Verschlusschrauben, metrisch



Explosion protection: II 2 G Ex e II
II 2 D Ex tD A21 IP68
Certificates: PTB 05 ATEX 1106
Protection class to EN 60 529: IP 68
Temperature range: -40°C to 120°C
Material: - Screw: Brass nickel-plated
- O-ring: EPDM



Explosionsschutz: II 2 G Ex e II
II 2 D Ex tD A21 IP68
Bescheinigungen: PTB 05 ATEX 1106
Schutzart gemäß EN 60 529: IP 68
Einsatztemperatur: -40°C bis 120°C
Material: - Schraube: Messing vernickelt
- O-Ring: EPDM

Type	WISKA-No. Nr.				TL
			mm	mm	mm
EX-EMVS 12	10065331	10	M 12x1,5	5	7,5
EX-EMVS 16	10065332	10	M 16x1,5	5	8
EX-EMVS 20	10065333	10	M 20x1,5	6	9
EX-EMVS 25	10065334	10	M 25x1,5	6,5	10
EX-EMVS 32	10065335	5	M 32x1,5	7	10,5
EX-EMVS 40	10065336	5	M 40x1,5	8	12
EX-EMVS 50	10065337	1	M 50x1,5	9	15
EX-EMVS 63	10065338	1	M 63x1,5	10	16