

RD, round wire; for lightning protection and earth-termination systems



hot-dip galvanized

item code	material	dn [mm]	L [m]	pl [kg]	ps [kg]	ref.
RD8fv	fv	8	125	500	50	006 818
RD10fv	fv	10	81	500	50	006 821



copper

item code	material	dn [mm]	spec.	L [m]	pl [kg]	ps [kg]	ref.
RD8Cu/w	Cu	8	soft	113	500	50	027 601
RD8Cu/hh	Cu	8	semi-hard	113	500	50	006 820



with plastic sheathing

item code	material	dn [mm]	spec.	L [m]	pl [kg]	ps [kg]	ref.
RD8fv/K	fv/K	8	-	113,5	500	50	085 064
RD8Al/K	Al/K	8	soft	100	300	20	061 422
RD10fv/K	fv/K	10	-	71,5	500	50	085 065



aluminium

item code	material	dn [mm]	spec.	L [m]	pl [kg]	ps [kg]	ref.
RD8Al/w	Al	8	soft	148	300	20	027 762
RD8Al/hh	Al	8	semi-hard	148	300	20	013 843



stainless steel

item code	material	dn [mm]	L [m]	pl [kg]	ps [kg]	ref.
RD8NiroV2A	V2A	8	125	500	50	085 066
RD8NiroV4A	V4A	8	148	500	50	085 067
RD10NiroV2A	V2A	10	80	500	50	085 068
RD10NiroV4A	V4A	10	80	500	50	085 069