

Data sheet

ID	AKG
Description	distribution box
Colour	white, similar to RAL 9010
Classification	AC 400 V



Norms: ÖVE/ÖNORM EN 60670-1:2014, ÖVE/ÖNORM EN 60670-22:2007



Working temperature	Degree of protection (IP)	UV-Level
-5 to +60 °C	IP30	L2

Art. no.	Dimensions Ø/LxB x T	For tube diameter	Small Package	Large Package
000 719	100 x 100 x 45 mm	-	50 pc	1750 pc
000 722	150 x 150 x 65 mm	-	25 pc	875 pc
000 724	200 x 200 x 70 mm	-	12 pc	288 pc
000 727	400 x 200 x 70 mm	-	5 pc	90 pc
000 726	400 x 400 x 70 mm	-	4 pc	72 pc

Details	
Halogen free	False
Tackable	False
Number of inlets	-
Type of housing feed-through	None
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	True
Weatherproof	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.