

Data sheet

| | |
|----------------|-------------------------------------------------------|
| ID | KSM BK |
| Description | slip type coupler |
| Properties | for sandthigt connections of KSR, BR and UDR ductings |
| Colour | black, similar to RAL 9005 |
| Classification | N 450 |



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Operating temperature
-5 bis +60 °C

UV-Level
L2

| Art. no. | Inner diameter | Outer diameter | Small Package | Large Package |
|----------|----------------|----------------|---------------|---------------|
| 001 930 | 50 mm | 53,7 mm | 100 pc | - |
| 001 931 | 63 mm | 67 mm | 60 pc | - |
| 001 932 | 75 mm | 79,6 mm | 37 pc | - |
| 001 933 | 90 mm | 95,5 mm | 22 pc | - |
| 001 934 | 110 mm | 116,3 mm | 12 pc | - |
| 001 935 | 125 mm | 132,7 mm | 7 pc | - |
| 001 936 | 140 mm | 148,8 mm | 6 pc | - |
| 001 937 | 160 mm | 169,5 mm | 3 pc | - |

Further technical details

Details

| | |
|--------------------|-----------|
| Surface protection | Untreated |
| Surface polished | False |
| Halogen free | False |
| Material | PVC-U |

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.