

Data sheet

ID	KSX BK
Description	cable ducting
Properties	plain, halogen-free in coils of 50 m resp. 100 m
Colour	black, similar to RAL 9005
Fire Behaviour	flame propagating
Classification	N 450



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Operating temperature
-30 bis +70 °C

UV-Level
L2

Art. no.	Outer diameter	Inner diameter	Small Package	Large Package
002 121	20 mm	16 mm	100 m	100 m
002 122	25 mm	21 mm	100 m	100 m
002 123	32 mm	28 mm	100 m	100 m
002 124	40 mm	35,2 mm	100 m	100 m
002 125	50 mm	44 mm	100 m	100 m
002 126	63 mm	55,4 mm	100 m	100 m
061 869	75 mm	66 mm	50 m	-
002 127	75 mm	66 mm	100 m	100 m
002 128	90 mm	79,4 mm	100 m	100 m
036 921	110 mm	97 mm	50 m	50 m

Further technical details

Details

Model	Pliable
Shape	Outer - and inner side plain
Surface protection	Untreated
Transparent	False
Material	PE

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.