



HLN, matice; černá (RAL 9005, UV-stabilní), metrický závit podle IEC/EN 60423





Objednávací pokyn: na vyžádání lze dodat závit Pg



HLN, matica; čierna (RAL 9005, UV - stabilná), metrický závit podľa IEC/EN 60423

Objednávacie pokyn: na vyžiadanie možnosť dodať závit Pg

materiál				tepl. rozsah
PPO				-45 °C/+150 °C
typ	dn	mb	vb	ref. č.
HLN 16	16,0	200	8000	014 485
HLN 20	20,0	200	8000	011 918
HLN 25	25,0	100	4000	011 919
HLN 32	32,0	100	2400	014 486
HLN 40	40,0	30	1200	019 823
HLN 50	50,0	25	1000	017 236



Parametry pro připojení trubek HFXP, HFXP-HT

Parametre pre pripojenie rúrok HFXP, HFXP-HT

Přímé vývodky

Priame vývodky

typ			L	A	D	dn
HGL 1212	M 12 x 1,5	21	8,0	18,3	21,0	12
HGL 1616	M 16 x 1,5	25	10,5	18,9	24,7	16
HGL 2020	M 20 x 1,5	30	12,0	24,0	29,8	20
HGL 2525	M 25 x 1,5	38	15,0	30,4	37,2	25
HGL 3232	M 32 x 1,5	45	15,0	32,0	45,0	32
HGL 4040	M 40 x 1,5	57	15,0	38,0	56,2	40
HGL 5050	M 50 x 1,5	68	15,0	42,4	68,0	50
HGL 6363	M 63 x 1,5	82	20,0	54,0	82,0	63

Úhlové vývodky

Uhlové vývodky

typ			L	A	B	D	dn
HEG 1212	M 12 x 1,5	21	8,0	28,3	39,0	21,0	12
HEG 1616	M 16 x 1,5	25	10,5	32,4	44,6	24,7	16
HEG 2020	M 20 x 1,5	30	12,0	39,5	52,4	29,8	20
HEG 2525	M 25 x 1,5	38	15,0	49,4	65,9	37,2	25
HEG 3232	M 32 x 1,5	45	15,0	60,0	77,4	45,0	32

Přírubové vývodky

Prírubové vývodky

typ	A	D	L	B	M	N	dn
HFL 20	35,9	29,8	65,0	41,0	33,0	27,0	20
HFL 25	42,0	37,2	75,9	45,0	37,0	30,0	25
HFL 32	50,0	45,0	90,0	56,0	46,0	37,0	32
HFL 40	62,0	56,2	110,5	70,0	58,0	45,0	40
HFL 50	76,0	68,0	129,3	84,0	72,0	55,0	50
HFL 63	96,0	82,0	162,0	98,0	84,0	70,0	63